

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Query Interactions

Query Interactions



- GET /customers/\${customer_id}/interactions
- GET /interactions/\${interaction_id}

Contents

- 1 Query Interactions
 - 1.1 Description
 - 1.2 Operation
 - 1.3 Response
 - 1.4 Example

Description

Retrieves multimedia interactions and their data.

Operation

Queries Multimedia Interactions

| ID | CV.WS.IXN.2 | | | |
|--------------------|---|---------------------------------|----------------------------------|--|
| Method | GET | | | |
| URL | By Customer: /customers/\${customer_id}/interactions By Interaction ID: /interactions/\${interaction_id} | | | |
| Name | Туре | Mandatory | Description | |
| URI Parameters | | | | |
| \${customer_id} | string | yes if query is by customer. | Customer ID, required for URI 1. | |
| \${service_id} | integer | yes if query is by service. | Service ID, required for URI 2. | |
| \${interaction_id} | integer | yes if query is by interaction. | Service ID, required for URI 3. | |



Important

The output sample shows a "structured_text" parameter which provides a URL to the structured text content (which is not returned as part of the query): the user application performs a separate GET to the given URL.

Similarly, the following URLs are available for GETting interaction content:

- /interactions/\${interaction_id}/plain_text
- /interactions/\${interaction_id}/structured_text
- /interactions/\${interaction_id}/binary_content

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this operation can return.

Response

| HTTP code | 200 | |
|--------------|--|--|
| HTTP message | OK | |
| Body | An array of one or more Interaction Resources. | |

Example

Operation

GET http://ucshost:8080/interactions/00001a57JGQ00BW8

Result

```
"external_id" : "00AF4A7951D60009",
"established_date" : "2009-08-05T09:33:15.000Z",
"text": "http://ucshost:8080/interactions/00001a57JGQ00BW8/plain text",
 "media_type" : "chat",
 "udata" : {
   "RTargetTypeSelected" : "2",
   "RRequestedSkillCombination" : "",
   "ChatServerHost" : "SUITE80",
"CustomerSegment" : "default",
   "RTargetObjectSelected" : "Agent Group Everybody",
"RTargetRuleSelected" : "",
"RTargetPlaceSelected" : "Place_1002",
   "RTargetAgentGroup" : "Agent Group Everybody",
"RTargetObjSelDBID" : "123",
   "ServiceType" : "default",
   " smsSrcNumber" : "+33298143456",
   "RTargetAgentSelected" : "1002",
   "RTenant" : "defaultTenant",
"RVQID" : "",
   "CBR-contract DBIDs" : "",
   "CBR-Interaction_cost" : "",
   "ChatServerPort": "23874",
"_smsDestNumber": "+33298143322",
"RTargetRequested": "Agent Group Everybody",
"CBR-IT-path_DBIDs": "",
   "RStrategyDBID" : "480",
   "CBR-actual_volume" : "",
   "RStrategyName" : "sms-session-inbound"
 "binary content" : "http://ucshost:8080/interactions/00001a57JGQ00BW8/binary content",
 "structured text" : "http://ucshost:8080/interactions/00001a57JGQ00BW8/structured_text",
"status" : 3,
"subject" : "SMS chat",
 "timeshift" : 1,
```

```
"type": "Inbound",
"interaction_id": "00001a57JGQ00BW8",
"allow_children": true,
"end_date": "2009-08-05T09:34:04.140Z",
"owner_id": 124,
"sub_type": "InboundNew",
"released_date": "2009-08-05T09:33:59.000Z",
"entity_type": 2,
"creator_app_id": 175,
"thread_id": "00001a57JGQ00BW9",
"start_date": "2009-08-05T09:33:10.000Z",
"structured_text_mime": "text/xml",
"customer_id": "00001a57JGQ00BVU"
}
```