



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Delete Metadata Identification Keys

Delete Metadata Identification Keys

Important

Prerequisites: You need to **enable** profiles in UCS.

```
/metadata/identification-keys/${id_key-name}
```

Contents

- [1 Delete Metadata Identification Keys](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)
 - [1.4 Example](#)

Description

Allows the deletion of Identification keys. The records in metadata table are removed, and the related table is dropped (if any). An identification key can be created based on the core profile attribute, but in this case a table is not created. Therefore, no table is dropped when it is deleted.

Operation

ID	CV.WS.PROF.META.8		
URI	/metadata/identification-keys/\${id_key-name}		
Method	DELETE		
Parameter	Type	Mandatory	Description
URI Parameter			
\${id_key-name}	string	yes	The metadata identification key name to delete. This name is not case-sensitive.

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

Response	
HTTP code	204
HTTP message	Success No Content

Example

The following operation deletes an identification key.

Operation

```
DELETE /metadata/identification-keys/idNickName
```

Result

HTTP/1.1 204 OK
Success No Content

Important

If nothing was deleted, HTTP status code 404 ("Not Found") is sent.