



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

[Get Metadata](#)

Get Metadata

Important

Prerequisites: You need to **enable** profiles in UCS.

GET \${content-type} /metadata

Contents

- [1 Get Metadata](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)
 - [1.4 Example](#)

Description

Returns the location for the list of available metadata resources.

Operation

Get Metadata

ID	CV.WS.META.1		
Method	GET		
URL	/metadata		
HEADER	\${content-type}		
Parameter	Type	Mandatory	Description
\${content-type}	"Content-type:text/html" "Content-type:application/json"	yes	The formatting for the returned result.

<references />

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

Response

HTTP code	200
HTTP message	OK
Body	GET "Content-type:text/html" /metadata Returns an HTML page, containing a list of resource links as follows: <pre><html><body><h1>Available Resources</h1>
 \${resource-name}
 </body></html></pre>

HTTP code	200
	where: • <code>\${resource}</code> is the location of the resource. • <code>\${resource-name}</code>, the name of the resource.
	GET "Content-type:application/json" /metadata Returns a JSON table, containing a list of resource links as follows: <pre>{ "\${resource-name-1}": "\${resource-1}", "\${resource-name-2}": "\${resource-2}", ... , "\${resource-name-n}": "\${resource-n}" }</pre> where: • <code>\${resource_i}</code> is the location of the resource-i. • <code>\${resource-name_i}</code> is the name of the resource-i.

Example

Operation

```
GET "Content-type:text/html" /metadata
```

Result

```
200 OK {
<html><body><h1>Available Resources</h1><br/>
<a href="http://localhost:8080/metadata/identification-keys">
identification-keys schemas<br/>
<a href="http://localhost:8080/metadata/tasks/extensions">Tasks Extensions<br/>
<a href="http://localhost:8080/metadata/states/extensions">States Extensions<br/>
<a href="http://localhost:8080/metadata/services/extensions">Services Extensions<br/>
<a href="http://localhost:8080/metadata/business-attributes">business-attributes mapping<br/>
</body></html>
}
```

Operation

```
GET "Content-type:application/json" /metadata
```

Result

```
200 OK
{"identification-keys schemas":"http://localhost:8080/metadata/identification-keys",
  "Tasks Extensions":"http://localhost:8080/metadata/tasks/extensions",
  "Services Extensions":"http://localhost:8080/metadata/services/extensions",
  "States Extensions":"http://localhost:8080/metadata/states/extensions",
  "business-attributes mapping":"http://localhost:8080/metadata/business-attributes"}
```