



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Delete Service By ID

Delete Service By ID

```
DELETE /services/${service_id}
```

Contents

- [1 Delete Service By ID](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)
 - [1.4 Example](#)

Description

Enables your application to delete a service if its ID is known.

Important

Your application needs a WRITE role to perform this request.

Operation

Method	DELETE		
URL	/genesys/1/cs/services/\${service_id}		
Field Name	Type	Mandatory	Description
URI Parameters			
\${service_id}	integer	yes	The service ID.

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

Response	
HTTP code	200
HTTP message	OK

<references />

Example

Operation The following operation deletes the given service with its active states and tasks.

DELETE http://localhost:8080/genesys/1/cs/services/361-a3793cef-d559-4f9f-a95d-64555a4ba371

Result

200 OK

In case of error, the result would have been:

```
400 Bad Request
{
  "message": "There are no service found for : 361-a3793cef-d559-4f9f-a95d-64555a4ba371",
  "exception": "com.genesyslab.gsg.services.contextservices.exceptions.NotFoundException"
}
```