



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Query Business Attribute Schema

12/14/2025

Query Business Attribute Schema

Important

Prerequisites: You need to **enable** profiles in UCS.

GET /metadata/business-attributes

Contents

- [1 Query Business Attribute Schema](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)
 - [1.4 Example](#)

Description

Returns the schema for the list of available business attributes.

Operation

ID	CV.WS.CONFIG.BA		
Method	GET		
URL	1. All: /metadata/business-attributes 2. /metadata/business-attributes/\${business-attribute-name} 3. /metadata/business-attributes?cv-attribute=\${attribute-full-name}		
Parameter	Type	Mandatory	Description
\${business-attribute-name}	string	no	The name of the business attribute, in order to retrieve its schema only.
\${attribute-full-name}	string	yes if ?cv-attribute= is part of the URL	The full name of a Context Services' business attribute in order to retrieve its schema. Examples: • Service.type, • Task.disposition, • State.media_type

<references />

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See **HTTP Response Codes and Errors** for further details on the possible codes that this operation can return.

HTTP code	200		
HTTP message	OK		
Parameter	Type	Mandatory	Description

HTTP code		200	
Body Business Attribute or BusinessAttribute[]			
name	string	yes	The business attribute's name.
dbid	string	yes	The business attribute's database ID.
display_name	string	yes	The business attribute's display name.
description	string	yes	The description.
map_name	boolean	no	• true means that the Business Attribute Value Names is returned instead of DB IDs in the responses for GET operations. • false means that DB IDs are returned in the responses for GET operations. See also [business-attributes] Section.
cv_attributes	string[]	no	The associated Context Services attributes.
values	BusinessAttribute[]	no	Nested possible attributes values.

Example

Operation

GET /metadata/business-attributes/MediaType

Result

```
200 OK {
{
  "display_name" : "Media Type",
  "values" : [ {
    "display_name" : "email",
    "description" : "Media EMail",
    "name" : "email",
    "dbid" : 1003
  }, {
    "display_name" : "chat",
    "description" : "Media Chat",
    "name" : "chat",
    "dbid" : 1006
  }, {
```

```
"display_name" : "voice",
"description" : "Media Voice",
"name" : "voice",
"dbid" : 1001
}, {
  "display_name" : "fax",
  "description" : "Media Fax",
  "name" : "fax",
  "dbid" : 1014
}],
"description" : "Media type identifier",
"name" : "MediaType",
"dbid" : 1001,
"map_name" : false,
"cv_attributes" : [ "Service.media_type", "State.media_type", "Task.media_type" ]
}
}
```