



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Composer Help

[Raise Event Block](#)

Raise Event Block

Contents

- **1 Raise Event Block**
 - 1.1 Name Property
 - 1.2 Block Notes Property
 - 1.3 Delay Property
 - 1.4 Unit Property
 - 1.5 Condition Property
 - 1.6 Logging Details Property
 - 1.7 Log Level Property
 - 1.8 Event Property
 - 1.9 Parameters Property
 - 1.10 Enable Status

Use the Raise Event block for Composer to throw custom events. You specify the event name and a message, which is selection of a dynamic variable. It is a terminating block (can end an application instead of an Exit block). Orchestration Server 8.1.2+ versions are required for Raise and Cancel Event blocks.

Also see [Custom Events](#).

The Raise Event block has the following properties:

The Raise Event block has no page exceptions.

Name Property

Find this property's details under [Common Properties for Callflow Blocks](#) or [Common Properties for Workflow Blocks](#).

Block Notes Property

Find this property's details under [Common Properties for Callflow Blocks](#) or [Common Properties for Workflow Blocks](#).

Delay Property

Enter the timeout or select a variable. Maps to <send delay>.

Unit Property

Select seconds or milliseconds for the delay. Maps to <send delay>.

Condition Property

Find this property's details under [Common Properties for Callflow Blocks](#) or [Common Properties for Workflow Blocks](#).

Logging Details Property

Find this property's details under [Common Properties for Callflow Blocks](#) or [Common Properties for](#)

Workflow Blocks.

Log Level Property

Find this property's details under [Common Properties for Callflow Blocks](#) or [Common Properties for Workflow Blocks](#).

Event Property

Select the variable or enter a value. Maps to <send event>.

Parameters Property

Add a list of key-values. Maps to <param>.

Enable Status

This property controls whether or not a block contributes code to the application. You may wish to use this property if there is a need to temporarily remove a block during debugging or, for other reasons during development, temporarily disable a block. This saves the effort of having to remove the block and then add it back later.