

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Composer Help

Composer Compared to IRD

Composer Compared to IRD

Contents

- 1 Composer Compared to IRD
 - 1.1 Integrated Development Environment
 - 1.2 Session-Based Versus Interaction-Based
 - 1.3 Differences from IRD
 - 1.4 Composer Routing Application Types
 - 1.5 Composer Blocks Mapped to IRD Objects

Here is a short video on the advantages of moving to Composer from Interaction Routing Designer as well as an interface comparison.

Composer Compared to IRD

Link to video

Integrated Development Environment

- Composer is a single Integrated Development Environment (IDE) for creating applications to routing
 interactions as well as to orchestrate the entire customer experience. Composer-created voice and
 routing applications can command and control the customer experience through all channels (IVR,
 voice, e-services, and so on).
- Composer's open framework enables widely-available, existing competencies to be used to create
 reusable components that manage the customer experience. The IDE allows both customers and
 integrators to utilize existing code sets (HTML, VXML, java, perl, REST and others) to control the
 customer experience.
- The open framework also allows simplified integration into all Enterprise applications to harness the information within the Enterprise to drive and personalize the customer experience.

Session-Based Versus Interaction-Based

Composer works with the Orchestration Server platform, which is session-based as compared to the Universal Routing Server (URS) platform, which is "interaction based.' A session can last for the length of the customer journey, across multiple interactions. URS only executes strategies (workflows) that interact on a single interaction. In contrast, ORS does not need to have an interaction to perform useful functionality. All ORS requires is an API call in order to execute. In this manner, the ORS platform can be thought of as a general purpose workflow platform to control the workflow regardless of whether or not you have an interaction (email, SMS, mobile, social, voice, and so on).

Differences from IRD

In the past, Universal Routing's Interaction Routing Designer was the only Genesys tool to create routing applications. Genesys Composer is now the tool of choice for creating both routing and voice self-service applications.

A few of the differences between Composer and Interaction Routing Designer are listed below.

- Composer is integrated with Orchestration Server allowing you to manage customer conversations spread out over time using the ORS session-based functionality and persistent storage as well as Orchestration Extensions.
- · Composer encompasses IRD's functionality and much more routing functionality in general.

- Composer lets you create routing applications using an open language (SCXML) and ECMAScript for decision-making. In contrast, IRD uses a closed Genesys proprietary language (IRL) and you are limited to IRD's objects and functions.
- Composer gives the option of writing your own SCXML code and/or using predefined blocks.
- Unlike IRD, you can also use Composer to create voice self-service applications for Genesys Voice
 Platform, including VoiceXML and CCXML-based applications. You can also create integrated voice and
 routing applications.
- Any routing application created in IRD can easily be created in Composer.

Composer Routing Application Types

You can use Composer's predefined blocks and/or write your own SCXML code to create routing applications that route based on various criteria such as:

- · Agent, Agent Group, ACD Queue, Place, Place Group, Route Point, Skill, or Variable
- last called agent
- date and time
- the value of a statistic.
- dialed number (DNIS)
- originating number (ANI)
- percent and conditional routing
- Service Level Routing

The above list is by no means complete. It represents only a few types of routing applications that can be created in Composer. Since Composer uses open languages (SCXML and ECMAScript), you are not limited to its pre-defined blocks, but are free to create many types of routing applications.

Composer Blocks Mapped to IRD Objects

Composer refers to the fundamental element of a workflow as a *block* whereas in IRD documentation, this element is referred to as an *object*. A few IRD object/Composer block equivalents are presented below. The tables group IRD objects based on their IRD toolbar category name and point to the corresponding functionality in Composer.

Tip

For a complete list of Composer blocks, including all those without an IRD equivalent, see RoutingBlockPaletteReference.

IRD Data & Services

IRD Object Name	Composer Block Name	Description
Database Wizard	DB Data	DB Data retrieves information from the database. Uses a Query Builder.
Web Service	Web Service	Invokes Web Services. GET, POST and SOAP over HTTPS are supported.
	Web Request	Invoke any supported HTTP web request or REST-style web Service. See sample: Routing Based on Web Request.

IRD Miscellaneous

IRD Object Name	Composer Block Name	Description
Assign Multi-Assign	Assign	Assigns a computed value/ expression or a literal value to a variable. Variables are defined in the Entry block. Capable of multiple assignments.
Call Subroutine	Subroutine	Creates reusable sub-modules.
Entry	Entry	Sets global error (exception) handlers. Defines global variables (see Variables section below) All routing strategy diagrams must start with an Entry block.
Exit	Exit	Terminates the strategy and returns control back to calling workflow in case of a subroutine.
Error Segmentation	Multiple error output ports can be created in Composer blocks based on each block's Exception property.	
Function Multi-Function	ECMAScript	Builds an ECMAScript expression using the Expression Builder. Many URS functions are available as Genesys Functional Modules described the Orchestration Server Documentation Wiki Can invoke multiple functions.
If	Assign, Branching, ECMAScriptBlock blocks all open Expression Builder	Expression Builder can be used to create IF expressions.
Multi-Attach	ECMAScript	Can be used for attaching data to an interaction.

IRD Routing

IRD Object Name	Composer Block Name	Description
Selection	Target	Routes an interaction to a target, which can be Agent, AgentGroup, ACDQueue, Place, PlaceGroup, RoutePoint, Skill, or Variable. Skill target uses Skill Expression Builder.
Percentage	Target	Statistics Order property in Target block, lets you perform percentage allocation. Also see sample: Routing Based on Percent Allocation.
Default	Default Route	Routes the interaction to the default destination.
Routing Rule		Orchestration Server 8.1 does not support service level routing rules.
Switch to Strategy		Orchestration Server 8.1 does not support switch to strategy routing rules.
Force Route	Force Route	Not exposed as a routing rule in Composer.
Statistics	Target	Although statistical routing rules are not yet supported as in IRD's Statistics routing object, users can use the Target object Statistic property to route based on the value of a statistic. A Statistics Manager and Builder let you create your own statistics from URS predefined statistics.

IRD Segmentation

IRD Object Name	Composer Block Name	Description
ANI	Branching	See YourFirstApplication: DNIS Routing for an example.
DNIS	Branching	See Your First Application: DNIS Routing for an example.
Date	Branching	See the sample: Routing Based on Date and Time.
Day of Week	Branching	See the sample: Routing Based on Date and Time.
Time	Branching	See the sample: Routing Based on Date and Time.
Classification Segmentation	Branching	For classification segmentation, an ECMAScript function

		determines if a particular category name or ID exists in the array of category objects represented by an application variable.
Generic	Branching	Use as a decision point in a workflow. It enables you to specify multiple application routes based on a branching condition.

Also see Context Services Blocks.

IRD Voice Treatment

See Composer Equivalent to IRD Treatment.

IRD Multimedia

See Composer Equivalent to IRD Treatment.

IRD Outbound

See Outbound Common Blocks

Context Services

See Context Services Blocks

Business Process

See Interaction Processing Diagrams Overview and Interaction Process Diagram Blocks.

Reusable Objects

- IRD List Object: See Composer's List Object Manager.
- IRD Variable List Dialog Box: See Entry block Variables property.

In contrast to IRD, which defines variables in a special dialog box outside of the strategy, Composer defines both workflow and Project variables.