



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Designer Help

Route Digital Block

12/15/2025

Contents

- 1 Route Digital Block
 - 1.1 Routing Tab
 - 1.2 Treatments tab
 - 1.3 Routing Priority tab
 - 1.4 Advanced tab
 - 1.5 Results tab
 - 1.6 Videos

Route Digital Block

If your application is a Digital type, you can use the **Route Digital** block in the **Assisted Service** phase to route interactions to an agent based on various criteria, such as skills.

You can sequentially place multiple **Route Digital** blocks with different settings, so that if routing fails in one block, your application proceeds to the next block.

When a **Route Digital** block successfully routes the interaction to an agent, the application moves to the **Finalize** phase, ignoring any subsequent blocks in the **Assisted Service** phase.

[Click here](#) to watch a video showing an example of skill-based routing for chat interactions.

Routing Tab

Select Routing type

Choose between the following routing options:

Skill based routing with relaxing criteria

Routes the interaction to an agent that has the required skills. If selected, you can choose from the following options:

- **Use system variables *RoutingSkills* and *RoutingVirtualQueue* set already in Menu Options** - Use system variables that were set in a [Menu Option](#) block.
- **Specify Skills in this block** - Specify one or more skills and a Virtual Queue to use to route this interaction. If you specified more than one skill, you can choose whether the routing engine considers **any** or **all** of the selected skills.

Important

This option uses the skill level specified in the **Skill Proficiency level** setting (documented below). For example, if you set an initial skill level of 8, Designer only routes the interaction to agents with the specified skills that have a level of 8 or greater. You cannot set an individual level for each specified skill.

- **Skill Proficiency level** - Enter the initial and minimum skill levels. The interaction is routed to an agent that has a skill level equal to or higher to the values provided. If you enable **Reduce skill requirements every**, you can have the skill level decremented by a certain amount every x number of seconds, until the minimum skill level is reached. This option allows you to expand the group of agents that can receive this interaction if other agents are busy.

Skill expression based routing

Enter a skill expression in the **Skill Expression** tab, or click the drop-down menu to select a variable that specifies a skill expression.

Application/Queue routing

Route the interaction to a specific application or queue.

Agent Group routing

Route the interaction to an Agent Group.

Agent routing

Route the interaction to agents by using a variable that holds the ID of an agent at runtime. You must use the following format: *agentid@optional_statserver.A*. Example: 1001@StatServer.A.

Other Routing Settings

Routing Algorithm

Select which algorithm is used to choose an agent when more than one agent is available. (For more information about the routing algorithms, see [Statistic Types](#) on the **Statistic** block page.)

Overall timeout

Enter the maximum time (in seconds) to wait for an agent to be available before moving to the next block. Optionally, you can enable the check box to specify a variable.

Important

System variables **SelectedTarget**, **SelectedVirtualQueue**, **SelectedComponent**, **SelectedTargetObject**, **SelectedAgent**, and **Access** are automatically set when the interaction is routed to an agent and can be used later in the application. Refer to the **Initialize** phase's **System Variables** tab to read a detailed description for each of these variables.

Example

Properties - Route



This block is used to route multimedia interactions based on skills. Skill proficiency levels to look for can be reduced gradually at regular intervals to look for less qualified and therefore more likely to find agents. Text messages, can be sent to the caller in a loop while the chat waits to be routed.



Routing



Treatments



Routing Priority



Advanced



Results

Select Routing type



Skill based routing with relaxing criteria



Use system variables 'RoutingSkills' and 'RoutingVirtualQueue' set already in Menu Options.



Specify Skills in this block

Choose Skills

GSYS_skill_2 X

GSYS_skill_3 X

Uses



all selected skills



any of selected skills

Select Virtual Queue

Gold_us-west-1 ▼

Skill Proficiency level

Initial Skill level ☐

8

Minimum Skill level ☐

1

☐ Reduce skill requirements every

30

sec by

1

level



Skill expression based routing



Application/Queue routing



Agent Group routing



Agent routing

Other Routing Settings

Routing Algorithm

Time in Ready State ▼

Order

Use Maximum Valt ▼

Overall timeout ☐

120

seconds. After this time, processing will move on to the next block.

Treatments tab

Use this tab to specify a busy treatment to execute while waiting for an agent to become available. The busy treatment can be a **Chat** message that you can set to repeat at regular intervals.

Example

Properties - Route



This block is used to route multimedia interactions based on skills. Skill proficiency levels to look for can be reduced gradually at regular intervals to look for less qualified and therefore more likely to find agents. Text messages, can be sent to the caller in a loop while the chat waits to be routed.



Routing



Treatments



Routing Priority



Advanced



Results

☒ Repeat treatmentsRepeat every ☐

15

seconds

[+ Add Chat](#)

Type	Value	Actions
Chat	<input type="text" value="Chat Message"/>	↑ ↓ ✖

Routing Priority tab

Use Priority during Routing

Enable this check box to use priority-based routing, which prioritizes your interactions depending on your business requirements.

To prioritize interactions, you must segment interactions and assign the name of that segment to a variable. You must select this variable in the **Lookup Priority table based on this variable** drop-down menu.

You can customize this table with your own segment definitions to fit your business needs. If the specific segment is not found, then the value specified for **Initial priority** is used. Enter a value in **Increment size** to increase the priority of an interaction that remains in a queue over time. The priority increment is defined for each segment, but a default increment is configurable with the **Increment Size** property.

Increment Priority every ____ seconds

Enable this check box to specify the time interval between priority increments. If you enable the other check box beside the field, you can select a variable that specifies the overall **Routing Timeout** and **Priority Increment Interval** properties.

Limit Priority to

If the **Increment Priority every ____ seconds** option is enabled, you can use this option to set a maximum priority value. For example, if the initial priority is 50, you can use this option to not let the priority value increase beyond 100.

If you enable the other check box beside the field, you can select a variable for this option.

Example

Properties - Route



This block is used to route multimedia interactions based on skills. Skill proficiency levels to look for can be reduced gradually at regular intervals to look for less qualified and therefore more likely to find agents. Text messages, can be sent to the caller in a loop while the chat waits to be routed.



Routing



Treatments



Routing Priority



Advanced



Results

☒ Use Priority during Routing☐ Increment Priority every seconds.Initial Priority

Lookup Priority table based on this variable

Define Priority segments in this table. The correct segment will be identified during the call and used.

[+ Add a Priority Segment](#)

Segment	Initial Priority	Increment Size	Maximum Priority	Delete
Gold	100	20	200	
Silver	80	15	160	
Bronze	60	10	120	

Advanced tab

Targeting

Clear targets from queue if this block times out

Enable this check box to specify whether the pending request for a target should be kept active or not after exiting this block on timeout. When the request is kept active (check box is disabled), an agent may be selected after the block times out if, for example, an agent with the matching criteria is ready after the block was exited.

Early exit from this block if no agents are logged in

Enable this check box to exit the block if no agents are logged in for the selected routing target (such as Agent or Agent Group, skill expression based, or skill based routing with relaxing criteria).

Threshold Expression

This option enables you to use an ECMAScript (or JavaScript) expression to further refine a routing threshold for the specified target(s). Threshold expressions for the **Route** block can be used for the following routing types:

- Skill
- Skill Expression
- Agent Group
- Agent
- Last Called Agent

Threshold expressions can contain variables or reference queue-specific values, such as *sdata(target, statistic)* or *callage()*. Strings must be enclosed in single quotes. For example:

Threshold Expression

For more information about using ECMAScripts in Designer, see [Assigning values to variables](#).

Important

For routing types that have multiple targets (such as Agent Group or Agent), the script defined in **Threshold Expression** applies to all targets.

Route only to local agents

If you have selected **Skill based routing with relaxing criteria** or **Skill expression based routing**, you can enable this option. When enabled, the call is routed to a local agent who matches the target skill.

Tip

If you want to route to local agents as the preferred option, but then route to all agents if there are no local agents available with the required skill, you can set up cascaded routing.

Here's a way you could do that:

- Set up the **Route** block with **Route only to local agents** enabled, a short **Overall timeout** property value, and **Clear targets from queue if this block times out** deselected.
- Then, set up any **Route** blocks that are further down the application flow with **Route only to local agents** not selected.

You can watch this video to see a short demonstration of how to set this up. (The video demonstrates this using a **Route Call** block, but the steps are the same.)

[Link to video](#)

You might also want to modify skill relaxing settings to run faster on routing blocks that target local agents.

In the **Post processing application** section, you can specify the digital application (queue) that will be used for post-processing logic. This application will be executed after the agent marks the chat as *done*.

Post-processing logic may include, for example, HTTP REST or Chat Transcript blocks.

Tip

If the purpose of your post-processing application is to only send a Chat Transcript, Genesys recommends that you use a **Terminate** block in the post-processing application to prevent it from sending of multiple copies of the transcript.

Example

Properties - Route



This block is used to route multimedia interactions based on skills. Skill proficiency levels to look for can be reduced gradually at regular intervals to look for less qualified and therefore more likely to find agents. Text messages, can be sent to the caller in a loop while the chat waits to be routed.



Routing



Treatments



Routing Priority



Advanced



Results

Targeting

☐ Clear targets from queue if this block times out.

There is no need to check this if routing attempt from this block should be considered in later routing blocks. Before checking this box, the implications to reporting must be considered.

☐ Early exit from this block if no agents are logged in.

When the block is exited because of the lack of logged in agent, the outcome variable error property is set to "noagentsloggedin". This will allow the application to optionally check if the cause of early exit was due to no logged in agents and take appropriate action.

In case of skill relaxation, this option will cause relaxation to happen sooner than the interval specified. If the last attempt also results in no logged in agents, the block will exit early.

Post processing application

Specify the Digital application to be used for post-processing logic.

This application will get executed after the agent marks the chat done. Post-processing logic may include for instance HTTP REST or Chat Transcript blocks.

Post processing application (queue) :

-- choose application (queue) --

Results tab

Select a variable in the **Store selected agent ID in this variable** drop-down menu to keep track in a specific variable the ID of the agent selected as a result of this **Route** block execution. The **SelectedAgent** system variable is transparently assigned this same agent ID value.

You can also select a variable in the **Store the outcome of the Route block in this variable** drop-

down menu to store the result of this **Route** block execution.

Videos

This video shows an example of using skill-based routing to route chat interactions.

[Link to video](#)