



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Chat Server Administration Guide

Deploying a Chat Solution

5/10/2025

# Deploying a Chat Solution

This page outlines the essential steps of deploying a Chat Solution.

## Overview

To deploy Chat Server, perform the following steps:

- Create a Chat Server application in configuration. Make sure that the following configuration is specified correctly:
  - **Ports.** At least 3 ports must be configured with the following IDs: default, webapi and ESP. Additionally, if KPI must be **exposed via REST API**, port with ID health must be added.
  - **Connections.** Chat Server must be connected to Interaction Server and UCS, and optionally Chat Server could be connected to the Configuration Server application (usually confserv) and Message Server. Setting addp is recommended for all these connections.
  - **Endpoints.** The endpoints:\*tenant\_dbid\* section must be renamed to contain an appropriate tenant ID value (for example endpoints:1) and the default option must be initialized with a queue name (to which Chat Server will submit interactions).
  - **Logs.** By default logs are configured to hide all possible sensitive data - which however might not be convenient if troubleshooting is required. Decide on how you want to set the hide-attached-data and message-log-print-size options in the settings section and options in the log-filter-data section.
- Set up **Chat Server High Availability** configuration if needed.
- Connect other applications to the Chat Server application:
  - **Interaction Server** must be connected to the ESP port (addp is recommended for this connection).
  - **GMS** must be connected to the webapi port (addp is not recommended for this connection due to short living nature of these connections).
- Install the Chat Server installation package (IP).
- Configure other applications to work with chat channels:
  - Create/modify **capacity** rule to include the chat media type.
  - Create/modify **workflow** (using either IR Designer or Composer) to route a chat interaction. For information about sending messages to a chat session refer to **How to Send Message or Notice to Chat Session from Workflow**.
  - Enable **GMS** to provide chat API (by adding the chat.customer-support section).
  - Configure **agents** (persons in configuration) with a chat channel access.
  - Adjust configuration of **Workspace** (agent desktop) if needed. For WDE review the chat.\* and chatserver.\* options and for the openmedia.workitem-channels option add the chat value.

## Interaction Server Cluster Support

Please refer to [Interaction Server Cluster](#) documentation (in particular, review [Special Considerations](#) for Media Servers in Suggested Deployment Configuration) in order to configure Chat Server to work with Interaction Server Cluster.

### Important

The [ESP Configuration Must Be Symmetrical](#) section means that in order to be able to send ESP messages from workflow to Chat Server using Interaction Server Cluster, each Interaction Server node in the cluster **must** have its own connection to ESP port of Chat Server.