



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Configurations Options Reference Manual

[common] Section

Contents

- 1 [common] Section
 - 1.1 enable-async-dns
 - 1.2 enable-ipv6
 - 1.3 rebind-delay

[common] Section

This section must be called **common**.

enable-async-dns

Default Value: 0

Valid Values:

| | |
|---|---------------------------------------------------|
| 0 | Disables asynchronous processing of DNS requests. |
| 1 | Enables asynchronous processing of DNS requests. |

Changes Take Effect: Immediately

Enables the asynchronous processing of DNS requests such as, for example, host-name resolution.

Important

- Use this option only when requested by Genesys Customer Care.
- Use this option only with T-Servers.

enable-ipv6

Default Value: 0

Valid Values:

| | |
|---|------------------------------------------|
| 0 | Off (default), IPv6 support is disabled. |
| 1 | On, IPv6 support is enabled. |

Changes Take Effect: Immediately

When set to 1, specifies that this application supports IPv6. It is set to 0 by default to ensure backward compatibility. Refer to component-specific documentation and the *Framework Deployment Guide* for more information about IPv6 and any specific considerations for deploying IPv6 in your situation.

rebind-delay

Default Value: 10

Valid Values: 0–600

Changes Take Effect: After restart

Specifies the delay, in seconds, between socket-bind operations that are being executed by the server. Use this option if the server has not been able to successfully occupy a configured port.

Important

Use this option only when requested by Genesys Customer Care.