



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Configurations Options Reference Manual

Genesys Deployment Agent Configuration File

12/19/2025

# Genesys Deployment Agent Configuration File

Genesys Deployment Agent supports common log options which allows you to precisely configure log output for it. Because you do not configure an **Application** object for Genesys Deployment Agent, if you need to change the default log option settings, create a configuration file called **gda.cfg** (or rename and modify the **gda.cfg.sample** file that is located in the installation folder) and specify new values for appropriate options. The file must be located in the same directory as the Genesys Deployment Agent executable file.

## Important

You can also specify a custom name for the configuration file using the **-c** command-line parameter. For example, **gda.exe -c gda\_custom.cfg**, where **gda\_custom.cfg** is the user-defined configuration file.

The Genesys Deployment Agent configuration file must have the following format:

```
[log]
<log option name>=<log option value>
<log option name>=<log option value>

[web]
rootdir=<path>
```

## Sample Configuration File

The following is a sample configuration file for Genesys Deployment Agent:

```
[log]
verbose = standard
standard = stdout, gdalog

[web]
rootdir=./gdaroot
```