



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Developer's Guide

<cfg:readObject>

<cfg:readObject>

Use <cfg:readObject> to read a configuration object. The child element <cfg:query> can select which object to read.

This action implies that only one object is to be read. If more than one object is to be read or searched, use the [<cfg:queryObjects>](#) element to return a list of configuration objects.

Contents

- [1 <cfg:readObject>](#)
 - [1.1 Child Elements](#)
 - [1.2 <cfg:readObject> with type="CfgAccessGroup"](#)
 - [1.3 <cfg:readObject> with type="CfgActionCode"](#)
 - [1.4 <cfg:readObject> with type="CfgAgentGroup"](#)
 - [1.5 <cfg:readObject> with type="CfgAgentLogin"](#)
 - [1.6 <cfg:readObject> with type="CfgAlarmCondition"](#)
 - [1.7 <cfg:readObject> with type="CfgApplication"](#)
 - [1.8 <cfg:readObject> with type="CfgAppPrototype"](#)
 - [1.9 <cfg:readObject> with type="CfgCallingList"](#)
 - [1.10 <cfg:readObject> with type="CfgCampaignGroup"](#)
 - [1.11 <cfg:readObject> with type="CfgCampaign"](#)
 - [1.12 <cfg:readObject> with type="CfgDNGroup"](#)
 - [1.13 <cfg:readObject> with type="CfgDN"](#)
 - [1.14 <cfg:readObject> with type="CfgEnumerator"](#)
 - [1.15 <cfg:readObject> with type="CfgEnumeratorValue"](#)
 - [1.16 <cfg:readObject> with type="CfgField"](#)
 - [1.17 <cfg:readObject> with type="CfgFilter"](#)
 - [1.18 <cfg:readObject> with type="CfgFolder"](#)
 - [1.19 <cfg:readObject> with type="CfgFormat"](#)
 - [1.20 <cfg:readObject> with type="CfgGVPIVRProfile"](#)
 - [1.21 <cfg:readObject> with type="CfgHost"](#)
 - [1.22 <cfg:readObject> with type="CfgIVRPort"](#)
 - [1.23 <cfg:readObject> with type="CfgIVR"](#)

- 1.24 <cfg:readObject> with type="CfgObjectiveTable"
- 1.25 <cfg:readObject> with type="CfgPerson"
- 1.26 <cfg:readObject> with type="CfgPhysicalSwitch"
- 1.27 <cfg:readObject> with type="CfgPlaceGroup"
- 1.28 <cfg:readObject> with type="CfgPlace"
- 1.29 <cfg:readObject> with type="CfgRole"
- 1.30 <cfg:readObject> with type="CfgScript"
- 1.31 <cfg:readObject> with type="CfgService"
- 1.32 <cfg:readObject> with type="CfgSkill"
- 1.33 <cfg:readObject> with type="CfgStatDay"
- 1.34 <cfg:readObject> with type="CfgStatTable"
- 1.35 <cfg:readObject> with type="CfgSwitch"
- 1.36 <cfg:readObject> with type="CfgTableAccess"
- 1.37 <cfg:readObject> with type="CfgTenant"
- 1.38 <cfg:readObject> with type="CfgTimeZone"
- 1.39 <cfg:readObject> with type="CfgTransaction"
- 1.40 <cfg:readObject> with type="CfgTreatment"
- 1.41 <cfg:readObject> with type="CfgVoicePrompt"

<cfg:readObject>

Child Elements

- <cfg:list>
- <cfg:parameter>
- <cfg:query>

<cfg:readObject> with **type**="CfgAccessGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—

<cfg:readObject> with **type**="CfgActionCode"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

<cfg:readObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject> with **type**="CfgAgentGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
name	string	—	—	—
tenantdbid	integer	—	—	—
dbid	integer	—	—	—

<cfg:readObject> with **type**="CfgAgentLogin"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

<cfg:readObject>

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
nopersondbid	integer	—	—	—
logincode	string	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgAlarmCondition"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject> with **type**="CfgApplication"

Attributes

<cfg:readObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
accountdbid	integer	—	—	—
accounttype	string	—	—	CfgObjectType
appprototypedbid	integer	—	—	—
subtype	string	—	—	CfgAppType
backupserverdbid	integer	—	—	—
dbid	integer	—	—	—
hostdbid	integer	—	—	—
isserver	string	—	—	CfgFlag
name	string	—	—	—
noclientdbid	integer	—	—	—
noswitchdbid	integer	—	—	—
port	integer	—	—	—
primaryserverdbid	integer	—	—	—
samehostandport	integer	—	—	—
serverdbid	integer	—	—	—
startuptype	string	—	—	CfgStartupType
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
version	string	—	—	—

<cfg:readObject> with **type="CfgAppPrototype"**

Attributes

<cfg:readObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
subtype	string	—	—	CfgAppType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
version	string	—	—	—

<cfg:readObject> with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
filterdbid	integer	—	—	—
logtableaccessdbid	integer	—	—	—
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>

Name	Type	Description	Default	Values
tableaccessdbid	integer	—	—	—
tenantdbid	integer	—	—	—
treatmentdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgCampaignGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
campaigndbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

<cfg:readObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callinglistdbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
name	string	—	—	—

<cfg:readObject> with **type**="CfgDNGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgDN"

Attributes

<cfg:readObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
association	string	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
number	string	—	—	—
subtype	string	—	—	CfgDNType
groupdbid	integer	—	—	—
ivrdbid	integer	—	—	—
name	string	—	—	—
noplacedbid	integer	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgEnumerator"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

<cfg:readObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
displayname	string	—	—	—
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultvalue	string	—	—	CfgFlag
displayname	string	—	—	—
enumeratordbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgField"

Attributes

<cfg:readObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
fieldtype	string	—	—	CfgFieldType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

<cfg:readObject> with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>

<cfg:readObject> with **type**="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultfolder	string	—	—	CfgFolderClass
folderclass	string	—	—	CfgFolderClass
name	string	—	—	—
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgFormat"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

<cfg:readObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
fielddbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
dbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

<cfg:readObject>

Name	Type	Description	Default	Values
subtype	string	—	—	CfgHostType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—
ostype	string	—	—	CfgOSType
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject> with **type="CfgIVRPort"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>

<cfg:readObject> with **type**="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
ivrserverdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

<cfg:readObject> with **type**="CfgObjectiveTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

<cfg:readObject>

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgPerson"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
employeeid	string	—	—	—
firstname	string	—	—	—
isagent	string	—	—	CfgFlag
lastname	string	—	—	—
logindbid	integer	—	—	—
nologindbid	integer	—	—	—
noplacedbid	integer	—	—	—
skilldbdbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
username	string	—	—	—
name	string	—	—	—

<cfg:readObject>

<cfg:readObject> with **type**="CfgPhysicalSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject> with **type**="CfgPlaceGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgPlace"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
nodndbid	integer	—	—	—
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

<cfg:readObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
rbacappns	string	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgScript"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgScriptType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
capacityagentdbid	integer	—	—	—
capacityagentgroupdbid	integer	—	—	—
capacityplacedbid	integer	—	—	—
capacityplacegroupdbid	integer	—	—	—
capacitytenantdbid	integer	—	—	—
dbid	integer	—	—	—
excludebytecode	string	—	—	CfgFlag
excludelongstrings	string	—	—	CfgFlag
name	string	—	—	—
subtype	string	—	—	CfgScriptType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>

<cfg:readObject> with **type**="CfgService"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

<cfg:readObject> with **type**="CfgSkill"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

<cfg:readObject>

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgStatDay"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
state	string	—	—	CfgObjectState
tabledbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject> with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

<cfg:readObject>

Name	Type	Description	Default	Values
name	string	—	—	—
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
statdaydbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
tserverdbid	integer	—	—	—

<cfg:readObject>

<cfg:readObject> with **type**="CfgTableAccess"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbaccessdbid	integer	—	—	—
dbid	integer	—	—	—
dbtablename	string	—	—	—
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

<cfg:readObject> with **type**="CfgTenant"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

<cfg:readObject>

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
alltenants	string	If included, regardless of value, returns the root tenant in the resultset. If excluded, the root tenant is not returned in the resultset.	—	CfgFlag
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject> with **type="CfgTimeZone"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
namemsexplorer	string	—	—	—
namenetscape	string	—	—	—
offset	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>

<cfg:readObject> with **type**="CfgTransaction"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callactioncode	string	—	—	CfgCallActionCode

<cfg:readObject>

Name	Type	Description	Default	Values
callresult	string	—	—	—
dbid	integer	—	—	—
destdndbid	integer	—	—	—
name	string	—	—	—
reactioncode	string	—	—	CfgRecActionCode
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject> with **type**="CfgVoicePrompt"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—