



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Deployment Guide

Including Additional JKS Parameters for SSO

4/7/2025

Including Additional JKS Parameters for SSO

If you want to use additional JKS parameters for SSO, follow the below procedure.

Procedure:

Steps

1. Create a backup of `gax.properties` file (`gax_bkp.properties`).
2. Empty the `gax.properties` file.
3. Start GAX. Access GAX in the same machine where it is installed using the url:
`http://localhost:8080/gax/`
4. Log in as a root user. Password is not required for this login.

Important

Do not close the browser tab until all the parameters are added.

5. Access `http://localhost:8080/gax/api/system/generategaxkey` in another browser tab. This creates the `gax_store.txt` file in the conf folder.
6. Access the below APIs to add encrypted parameters in the `gax.properties` file:
`http://localhost:8080/gax/api/system/setsamljkspassword?password=<PASSWORD>`
`http://localhost:8080/gax/api/system/setsamlsigningkeyname?name=<NAME>`
`http://localhost:8080/gax/api/system/setsamlsigningkeypassword?password=<PASSWORD>`
7. Add the existing parameters from the backup file `gax_bkp.properties` to `gax.properties` file and save it.
8. Now, follow the steps provided in the [Enabling SSO](#) section to enable the SSO feature.