



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Deployment Guide

security Section

security Section

Contents

- [1 security Section](#)
 - [1.1 enable_un_cookie](#)
 - [1.2 host_whitelist](#)
 - [1.3 host_whitelist_enabled](#)

This section must be called `security`, and is configured in the Genesys Administrator Extension Server Application object of type **Genesys Administrator Server**.

The options in this section relate to security features in Genesys Administrator Extension.

`enable_un_cookie`

Default Value: `false`

Valid Values: `true`, `false`

Changes Take Effect: After restart

Specifies if the encrypted usernames are stored in the browser cookies. If set to `true`, GAX stores the encrypted username in browser cookies for a period of 30 days. If set to `false`, GAX does not store the username in the browser cookies and it also removes the existing username (un) cookies.

`host_whitelist`

Default Value: Empty

Valid Values: URLs of hosts trusted by this GAX instance, separated by semi-colons (;); for example `132.56.54.34;host1;34.32.12.8`

Changes Take Effect: After restart

Specifies the host URLs that can be whitelisted. This option only takes effect when **`host_whitelist_enabled`** is set to `true`.

`host_whitelist_enabled`

Default Value: `false`

Valid Values: `true`, `false`

Changes Take Effect: After restart

Specifies if host whitelisting is enabled in GAX. If this option is not set or set to `false` (the default), then host whitelisting is disabled and all hosts are allowed by GAX.

If set to `true`, only those hosts specified in the option **`host_whitelist`** can appear as:

- values of the parameters **`logout_success_url`**, **`logout_failure_url`**, and **`logout_url`** when **logging in remotely**
- list of hosts from which to select **UNC Path to Mounted CD or Directory**, **UNC Path to an Existing Administrator Repository**, and **UNC Path to Zipped IPs** when **uploading IPs**.