



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Deployment Guide

cross-origin Section

## cross-origin Section

### allowedOrigins

Default Value: "\*"

Valid Values: List of origins in the format <scheme>://<domain>[:<port>]

For example:

- "http://\*.genesys.com"
- "http://intranet.domain.com:8700,http://<host>:<port>,http://<ip\_address>"

Changes Take Effect: Immediately

A comma separated list of origins, such as instrumented web sites, allowed to access the Co-browse Server. If an allowed origin contains one or more "\*" characters (for example, http://\*.domain.com), then "\*" characters are converted to ".\*". Any "." characters are converted to "\.". The resulting allowed origin can be interpreted as a regular expression.

### disableHttpRequest

Default Value: false

Valid Values: true or false

Changes Take Effect: Immediately

### **Available starting with Co-browse Server 8.5.003.07**

If set to true, disables all HTTP OPTIONS requests.

Disabling HTTP OPTIONS may slightly affect performance as it blocks the long-polling transport, which needs OPTIONS requests. Generally, Genesys does not advise you disable HTTP OPTIONS unless required by your security policies.