



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Deployment Guide

Start and Stop Genesys Co-browse Server

12/19/2025

Start and Stop Genesys Co-browse Server

Contents

- [1 Start and Stop Genesys Co-browse Server](#)
 - [1.1 Start the Co-browse Server](#)
 - [1.2 Stop the Co-browse Server](#)

Start the Co-browse Server

Select a tab below to start Co-browse Server on either Windows or Linux:

Windows

Start the Co-browse Server on Windows

Important

You can start the Genesys Co-browse Server on Windows from:

- Windows Services
- the startserver.bat script
- the cobrowse.bat script
- Genesys Administrator

Start

- You can start the server from Windows Services.
 1. Open Windows Services
 2. Select and start the Co-browse Server service.
- You can use the provided startserver.bat script.
 1. Navigate to the Co-browse installation server directory and launch the Windows command console (cmd.exe).
 2. Type and execute startserver.bat, without any parameters.
- You can use the provided cobrowse.bat script.
 1. Navigate to the Co-browse installation server directory and launch the Windows command console (cmd.exe).
 2. Type and execute cobrowse.bat, along with the '-host', '-port', and '-app' parameters. For example,
cobrowse.bat -host demosrv.genesyslab.com -port 2020 -app Co-browse_Server
You can find your parameters in the Server Info section of your Co-browse application in Genesys Administrator.
- You can start the server from Genesys Administrator.

1. Navigate to PROVISIONING > Environment > Applications.
2. Select the Co-browse Server.
3. Click Start applications in the Runtime panel.

End

The Genesys Co-browse Server is shown in Started status in Genesys Administrator.

Linux

Start the Co-browse Server on Linux

Important

You can start the Genesys Co-browse Server on Linux from:

- the run.sh script
- the cobrowse.sh script
- Genesys Administrator

Start

- You can use the provided run.sh script.
 1. Navigate to the Co-browse installation root directory in the Linux command console.
 2. Type and execute run.sh, without any parameters.
- You can use the provided cobrowse.sh script.
 1. Navigate to the Co-browse installation server directory in the Linux command console.
 2. Type and execute cobrowse.sh, along with the '-host', '-port', and '-app' parameters. For example, cobrowse.sh -host demosrv.genesyslab.com -port 2020 -app Co-browse_Server. **Note:** You can start the application as a daemon by adding -d to the command.
You can find your parameters in the Server Info section of your Co-browse application in Genesys Administrator.
- You can start the server from Genesys Administrator
 1. Navigate to PROVISIONING > Environment > Applications.
 2. Select the Co-browse Server.
 3. Click Start applications in the Runtime panel.

End

The Genesys Co-browse Server is shown in Started status in Genesys Administrator.

Stop the Co-browse Server

Select a tab below to stop Co-browse Server on either Windows or Linux:

Stop the Co-browse Server on Windows

Stop the Co-browse Server on Windows

Important

You can stop the Genesys Co-browse Server on Windows from:

- Windows Services
- Genesys Administrator
- A console window

Start

- You can stop the server from Windows Services.
 1. Open Windows Services
 2. Select and stop the Co-browse Server service.
- You can stop the server from Genesys Administrator.
 1. Navigate to PROVISIONING > Environment > Applications.
 2. Select the Co-browse Server.
 3. Click Stop applications in the Runtime panel.
- If you previously started Co-browse Server in a console window, you can stop the server by closing the window.

End

The Genesys Co-browse Server is shown in Stopped status in Genesys Administrator.

Stop the Co-browse Server on Linux

Stop the Co-browse Server on Linux

Important

You can stop the Genesys Co-browse Server on Linux from either **Genesys Administrator** or a **console window**.

Start

- You can stop the server from Genesys Administrator.
 1. Navigate to PROVISIONING > Environment > Applications.
 2. Select the Co-browse Server.
 3. Click Stop applications in the Runtime panel.
- Or you can stop the server from the console window where it was started.
 1. Press Ctrl+C while the window is active.
 2. Type Y and press Enter.

End

The Genesys Co-browse Server is shown in Stopped status in Genesys Administrator.