

GENESYS[®]

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Customer Experience Insights User's Guide

Callback Details Report

4/25/2025

Contents

- 1 Callback Details Report
 - 1.1 Understanding the Callback Details Report
 - 1.2 Prompts for the Callback Details Report
 - 1.3 Attributes used in the Callback Details Report
 - 1.4 Metrics used in the Callback Details Report
 - 1.5 Customize the report to filter by Desired Time and Dial Result

Callback Details Report

This page describes how you can use the (**Callback** folder) **Callback Details Report** to understand overall callback success rates in your contact center. It shows detailed information about the number and percentage of offered callbacks that were successful, versus how many were declined, canceled, or abandoned. Reporting on declined callback offers is available in Genesys Engage cloud deployments only.

Understanding the Callback Details Report

Tenant	Queue	Service	ID	Customer Phot	e Number	Final	offered	Accepted		ce Start estamp	Ready to Star Timestamp	conn	tomer ected stamp	Callback Times		of	Callback fered estamp	Callbac Accepte Timesta	d Con	£1
		HEIIKJS63569LDP80P79LASLUS000001		6666000		0	1	1	11/06/201	14 19:31:30 1	11/06/2014 19:31	1:48 11/06/201	4 19:31:48	11/06/2014	19:31:30	11/06/20	14 19:31:30	11/06/2014 19	0:31:48	1
						1	1	1	11/06/201	14 19:31:30 1	11/06/2014 19:32	11/06/201	4 19:33:02	11/06/2014	19:31:30	11/06/20	14 19:31:30	11/06/2014 19	0:31:49	1
	_					0	1	1	11/06/201	14 20:00:17 1	11/06/2014 20:00	11/06/201	4 20:00:31	11/06/2014	20:00:17	11/06/20	14 20:00:17	11/06/2014 20	0:00:31	1
	þ	Callback with mine offer mine offer mine within mine Position Transfer Added Abandoned															Callback			
		Confirmed Timestamp	To Start Timestamp	Attempts	Wait T: (Pmt)		(Fmt)	Offer (Fr		Waiting Time (Pmt)	Time (Fmt)	Waiting Time (Pmt)	Time (Pmt)	Position in Queue	Transfer Failed		Abandoned Waiting	Waiting (Fmt)	Agent Assistance	Offers per Session
	1			c	00:00		00:00:19		00:00:19	00:00:00		00:00:00	00:00:19	0	(0 0	0		1	
	19			2	00:00		00:00:19		00:00:19	00:01:13		00:00:06	00:00:19	1		1	0	00:00:00	1	
	31			c		0:00	00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0	(0 0	0		1	
	1:32			2		0:00	00:00:1		00:00:15	00:01:11		00:00:06	00:00:15	1		0 1	0		1	
	5:55			C		0:00	00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0		0 0	0	00:00:00	1	
vironment	15:56			1	00:00		00:00:1		00:00:15	00:00:41		00:00:00	00:00:15	1	0	0 0	1	00:00:00	1	
	52:14			C	00:00		00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0		0 0	0	00:00:00	1	
	52:15			1	00:00		00:00:1		00:00:15	00:00:41		00:00:00	00:00:15	1		0 0	1	00:00:00	1	
	8:33			0		0:00	00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0	(0 0	0	00:00:00	1	
	8:33			3		0:01	00:00:1		00:00:15	00:01:41		00:00:06	00:00:15	1		1	0		1	
	56			0		0:00	00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0		0 0	0	00:00:00	1	
	10			3	0:00		00:00:1		00:00:15	00:01:41		00:00:06	00:00:15	1			0	00:00:00	1	
	1			2	00:0		00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	1) U	0	00:00:00	1	
	1			4	00:0		00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	1		2 0	0	00:00:00	1	
				2										1			0		1	
	- 1-			2	00:00	0:02	00:00:1		00:00:15	00:01:11		00:00:06	00:00:15	1			0	00:00:00	1	
	- l-					0:00	00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0			0		1	
						0:00	00:00:1		00:00:15	00:00:00		00:00:00	00:00:15	0) 0) 0	0		1	
	133				0010		00:00:15		00:00:15	00:00:00		00:00:00	00:00:15	0) 0) 0	0		1	
	8,15				0010		00:00:15		00:00:15	00:00:00		00100100	00:00:15	0		0 0	0	00:00:00	1	
	28:32					0:00	00:00:15		00:00:15	00:00:00		00:00:00	00:00:15	0		0 0	0	00:00:00	1	
	28:32			2		0:01	00:00:15		00:00:15	00:00:00		00:00:00	00:00:15	1			1		1	
	85:19			-		0:00	00:00:15		00:00:15	00:00:00		00100100	00:00:15	0		0 0	0		1	
	5:19			2		0:01	00:00:15		00:00:15	00:00:00		00100100	00:00:15	1		0 0	1	00100100	1	
	1.05			-		0:00	00:00:15		00:00:15	00:00:00		00:00:00		0			0	00:00:00	1	

This report provides detailed information about callbacks that were processed by the contact center, allowing you to analyse callback performance based on nearly 30 metrics. Use this report to view a detailed picture of how Callback is used in your contact center, including information about the volume of callback calls, success rates, resulting savings, and customer wait times.

To get a better idea of what this report looks like, view sample output from the report: HRCXICallbackDetailsReport.pdf

The following tables explain the prompts you can select when you generate the report, and the metrics and attributes that are represented in the report:

Prompts for the Callback Details Report

Prompt	Description
Pre-set Day Filter	Choose a day from the list of preset options. This prompt overrides the Start Time and End Time values.
Start Time	Choose the day and time from which to begin collecting data into the report. This prompt has no effect if Pre-set Day Filter is set to anything except None .
End Time	Choose the day and time at which to stop collecting data into the report.
Final or Not	Enter 1 to restrict the report to only those calls where callback was dialed, or enter 0 to include all scheduled Callbacks, even if they were never dialed.
Queue	Select one or more queues from which to gather data into the report. Default: ALL
Customer Phone Number	Select one or more customer phone numbers for which to gather data into the report. Default: ALL
Tenant	Select one or more tenants to include in the report. Default: ALL

Attributes used in the Callback Details Report

Attribute	Description
Tenant	Enables data within the reporting interval to be organized by tenant. For multi-tenant environments, the universe connection that you define points to only one tenant schema in the Info Mart. New connections are required for access to other tenant schemas.
Queue	Enables data within the reporting interval to be organized based on the name of the virtual queue.
Service ID	Enables data within the reporting interval to be organized based on the original SCXML/GMS session ID.
	Enables data to be organized based on the phone number provided by the customer for callback.
Customer Phone Number	This number is used to dial out (CUSTOMER_TERMINATED scenario) or used to execute match by ANI (CUSTOMER_ORIGINATED scenario).
Forced Dialed	Enables data to be organized based on whether the callback queue is being flushed, and dialing (or push notification) is being forced regardlss of actual agent availability. $(0 = No, 1 = Yes)$.

Attribute	Description
	A value of 1 (yes) might occur at the end of the day, when contact center personnel are trying to close the queue for the day and do not want to leave any callbacks for the next day.

Metrics used in the Callback Details Report

Metric	Description						
Offered	Indicates whether callback was offered to the customer. $(0=no, 1=yes)$						
Accepted	Indicates whether callback was accepted by the customer. $(0=no, 1=yes)$						
Service Start Timestamp	The date and time (UTC) when the Callback service started.						
Ready To Start Timestamp	Either: The time when the contact center was ready to start the outbound dial attempt for CUSTOMER_TERMINATED scenarios. or: The time when the contact center sent push notification to the user device in CUSTOMER_ORIGINATED scenarios.						
Customer Connected Timestamp	The time when the customer started waiting to be connected to an agent.						
Callback Offered Timestamp	The time when the customer was first offered callback during the session.						
Last Callback Offered Timestamp	The date and time of the last callback offered to a customer during the session.						
Callback Accepted Timestamp	The time when the customer accepted callback during the session.						
Push Delivery Confirmed Timestamp	The time when the application confirmed that push notification was received. This is used for CUSTOMER_ORIGINATED scenarios.						
Customer Ready to Start Timestamp	The time when the customer was ready to start media interaction for CUSTOMER_ORIGINATED scenarios. This value is typically set when the application sends a request for an access number to dial and access code for match function.						
Desired TimeStamp	The callback time that was promised to the customer when callback was scheduled.						
Callback Attempts	The number of times the system attempted to call the customer back.						
Expected Wait Time (Fmt)	The customer expected wait time when the callback dial attempt was ready to begin.						
Callback Offer Time (Fmt)	The amount of time that elapsed between the						

Metric	Description					
	instant when a callback was offered to the customer, and the instant when the customer accepted or declined the offer.					
Last Callback Offer Time (Fmt)	The duration (in seconds) of the last callback offered to a customer during the session.					
Offline Waiting Time (Fmt)	The amount of time that elapsed between when the customer accepted a callback offer and the time when they were connected to an agent after callback.					
Establish Time (Fmt)	The amount of time required to establish the outbound call.					
Connect Waiting Time (Fmt)	The amount of time that elapsed between when the customer connected to the callback call and when an agent was connected.					
Position in Queue	The customer's position in the queue when the callback outbound dial attempt was ready to begin					
Transfer Failed	The number of failed attempts to transfer the callback interaction to the agent.					
Added Agent	Indicates whether an agent was successfully added to the callback call. $(0=no, 1=yes)$					
Abandon Waiting	Indicates whether the call was abandoned by the customer while waiting for an agent to connect. $(0=no, 1=yes)$					
Timeout Waiting (Fmt)	The number of times that a customer was disconnected because the max timeout limit was reached.					
Requested Agent Assistance	The number of callbacks that were offered to customers who had requested agent assistance. $(0=no, 1=yes)$					
Callback Offers per Session	The number of times callback was offered, per single interaction.					

Customize the report to filter by Desired Time and Dial Result

Report Home 🔻 Tools 👻 Data	- GRID	FORMAT	•									
8 🛧 🖈 👱 🛄	# *	□ <	: 8	i	6	í.	퀧	ŝ	**			
L OBJECTS ? ×												
Detail 🗸 🖬 📴												
▼ Q		Queue	Service ID					Customer			Forced	
Custom	Tenant								one nber	Final	Dialed	(
Abandoned Waiting								Nu	inner			
Accepted				0.5501.01								
Added Agent			HEIIKJS63569LDP80P79LASLUS000001					6666	000	1	No	
Callback Accepted Timestamp			HEIIKJS63569LDP80P79LASLUS000002					6666	000	1	Yes	I
Callback Attempts			12					000000				1
Callback Dim 4 Key			HEIIKJS63569LDP80P79LASLUS000003							1	No	
Callback Offer Time												
Callback Offered Timestamp			HEIIKJS63569LDP80P79LASLUS000004							1	No	ł
Callback Offers per Session			HEIIKJS63569LDP80P79LASLUS000005							1	Yes	1
Connect Waiting Time			TEIN000000000000000000000000000000000000								163	
Customer Connected Timestamp			HEIIKJS63569LDP80P79LASLUS000006							1	Yes	
Customer Ready To Start Timestam												
Desired Time			HEIIKJS63569LDP80P79LASLUS000007							1	No	
Desired Time			HEIIKJS63569LDP80P79LASLUS000008							Vez		
Desired Timestamp									1	Yes		
Dial Result			HEIIKJS63569LDP80P79LASLUS000009					6666	000	1	No	
Establish Time								5000				
Expected Wait Time			HEIIKJS6	3569LDF	P80P79	LASLUS	600000A	6666	000	1	Yes	
Expected Wait Time when Offered												
Final			HEIIKJS6	3569LDF	P80P79	LASLUS	S00000B	6666	000	1	Yes	
Forced Dialed		8666	HEIIKJS63569LDP80P79LASLUS00000C					6666	000	1	Vec	
Last Callback Offer Time	Environment		HEIKJS63569LDP80P79LASLUS00000C					6666	000	1	Yes	
h Last Callback Offered Timestamp	Controlle	0000	HEIIKJS63569LDP80P79LASLUS00000D							1	Yes	
1 <u>2</u> of 2 pages ▶												1
7 items found			HEIIKJS6	3569LDF	P80P79	LASLUS	S00000E	6666	6666	1	No	ł
REPORT OBJECTS			HEIIKJS63569LDP80P79LASLUS00000F				6666	000	1	No		
ALL OBJECTS												ł
MDX OBJECTS			HEIIKJS6	3569LDF	P80P79	LASLUS	s00000G	6666	6666	1	Yes	ł
NOTES											Ves	1

Use this procedure to customize this report to organize callback information based on the callback time customers requested, and result of the callback attempt.

Important

Note that filtering by Desired Time can decrease SQL performance. Genesys recommends running a report with this modification over a limited period of time, such as one day or less.

- 1. Log in with an account having Administrator privileges.
- 2. Open and run the Callback Details report.
- 3. In the **Save As** editor:
 - 1. Click **Report Home > Save As**.
 - 2. In the **Save in** field, choose either: **Shared Reports** > **Custom** to make the new report accessible to other users, or **My Reports** to make the new report accessible only to you.
 - 3. Enter a **Name** for the report, such as **Callback Details By Desired Time**, and optionally modify the **Description**, or **Advanced Options**.
 - 4. Click **OK**.
- 4. In the Report Saved editor, click Run newly saved report.
- 5. The prompts page opens; make appropriate selections and click **Run Report**. You can now modify the report:
- 6. In the menu, click **Grid** > **Design** to view the Report Objects Editor (if it's not already visible).
- Click All Objects, and browse to GCXI > Callback. Note that objects in the folder are sorted alphabetically; use the controls at the bottom of the list to see additional objects.
- 8. To organize the data based on the callback time that customers requested:
 - 1. From the list of available objects, drag the attribute **Desired Time** into the filter panel, and set the input value for it to **Between (enter value 1;value2)**.
 - 2. Drag the existing **Pre-set and Day and Time Range** and **Pre-set and Day and Time Range(Callback)** filters out of the panel, to remove them from the report.
- 9. To organize the data based on the result of the callback attempt:
 - 1. From the list of available objects, drag the attribute **Dial Result** into the report grid.
 - 2. Select forms if required.
- 10. Once you have finished editing the report, click **Save**, and re-run the report to test your changes.

For more information about customizing Genesys CX Insights, see Customizing reports.

Attributes used in this procedure

Attribute	Description
Dial Result	Enables data to be organized based on the dialing result. Values=BUSY, NO_ANSWER, ANSWERING_MACHINE, ERROR_TONE, FAX, PERSON, REDIAL_LIMIT_REACHED.
Desired Time	Enables data to be organized based on the callback time requested by the customer.

For more information about objects you can use to customize Callback reports, see Callback in the Genesys CX Insights Projects Reference Guide.