

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Info Mart Physical Data Model for an Oracle Database

Table CAMPAIGN GROUP SESSION FACT

Table CAMPAIGN_GROUP_SESSION_FACT

Description

Modified: 8.5.015.19 (PRODUCER_BATCH_ID added); 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is partitioned.

Each row represents an outbound campaign group session, where a session is started when a campaign group is loaded and ended when a campaign group is unloaded. The grain of the fact is an accumulating snapshot that represents the duration of the campaign group session.

Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: Download a CSV file.

Hint: For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

Column List

Legend

Column	Data Type	Р	M	F	DV
CAMP_GROUP_SI	ESSUMBER (II)KEY	Χ	X		
GROUP_KEY	NUMBER(10)		X	Χ	
CAMPAIGN_KEY	NUMBER(10)		X	Χ	
TENANT_KEY	NUMBER(10)		X	X	

Column	Data Type	Р	M	F	DV
START_DATE_TIM	ENKEMBER(10)		X	X	
END_DATE_TIME_	MEMMBER(10)		X	X	
CREATE_AUDIT_k	EMUMBER(19)		X	X	
UPDATE_AUDIT_k	CENUMBER(19)		X	X	
START_TS	NUMBER(10)				
END_TS	NUMBER(10)				
TOTAL_DURATION	N NUMBER(10)				
CAMPAIGN_GROU	JPSESTION_ID4 CHAR)				
ACTIVE_FLAG	NUMBER(1)				
PURGE_FLAG	NUMBER(1)				
PRODUCER_BATO	CHNUMBER(19)				

CAMP_GROUP_SESSION_FACT_KEY

The primary key of this table.

GROUP_KEY

The surrogate key that is used to join the GROUP dimension to the fact tables.

CAMPAIGN KEY

The surrogate key that is used to join the CAMPAIGN dimension to the fact tables.

TENANT KEY

The surrogate key that is used to join the TENANT dimension to the fact tables.

START_DATE_TIME_KEY

Identifies the start of a 15-minute interval in which the campaign group session began. Use this value as a key to join the fact tables to any configured DATE_TIME dimension, in order to group the facts that are related to the same interval and/or convert the START_TS timestamp to an appropriate time zone.

END DATE TIME KEY

Identifies the start of a 15-minute interval in which the campaign group session ended. Use this value

as a key to join the fact tables to any configured DATE_TIME dimension, in order to group the facts that are related to the same interval and/or convert the END_TS timestamp to an appropriate time zone.

CREATE AUDIT KEY

The surrogate key that is used to join to the CTL_AUDIT_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools — that is, applications that need to identify newly added data.

UPDATE AUDIT KEY

The surrogate key that is used to join to the CTL_AUDIT_LOG control table. The key specifies the lineage for data update. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools — that is, applications that need to identify recently modified data.

START TS

The UTC-equivalent value of the date and time at which the campaign group session began.

END_TS

The meaning depends on the value of ACTIVE_FLAG. For an inactive row, this field represents the UTC-equivalent value of the date and time at which the campaign group session ended. For an active row, this value represents a UTC-equivalent value of the date and time far in the future, so that applications do not have to test for null.

TOTAL DURATION

The meaning depends on the value of ACTIVE_FLAG. For an inactive row, the total duration, in seconds, of the campaign group session. For an active row, the duration, in seconds, that the campaign group session was active, from start time to the time that the ETL last executed.

CAMPAIGN_GROUP_SESSION_ID

The ICON source SessID for the campaign group session with which this session fact is related.

ACTIVE_FLAG

Indicates whether the campaign group session is currently active: 0 = No, 1 = Yes.

PURGE_FLAG

This field is reserved.

PRODUCER_BATCH_ID

Introduced: Release 8.5.015.19 Reserved for internal use.

Index List

CODE	U	С	Description
I_CGSEF_SID	X		Ensures that the facts that are stored in the table are for unique sessions.
I_CGSEF_DT			Improves access time, based on the Start Date Time key.
I_CGSEF_TNT			Improves access time, based on the Tenant.

Index I_CGSEF_SID

Field	Sort	Comment
CAMPAIGN_GROUP_SESSION_ID	Ascending	
START_DATE_TIME_KEY	Ascending	

Index I_CGSEF_DT

Field	Sort	Comment
START_DATE_TIME_KEY	Ascending	
END_DATE_TIME_KEY	Ascending	

Index I_CGSEF_TNT

Field	Sort	Comment
TENANT_KEY	Ascending	

Subject Areas

- Campaign_Group_Session Represents campaign groups as they are being loaded and unloaded.
- Facts Represents the relationships between subject area facts.