

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## Genesys Info Mart Physical Data Model for an Oracle Database

Table CTL ETL HISTORY

# Table CTL\_ETL\_HISTORY

#### Description

**Modified:** 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is partitioned.

This table provides information about the execution of each Genesys Info Mart job. A row is added to this table after each job completes.

#### Tip

Genesys recommends that you use the ADMIN\_ETL\_JOB\_HISTORY view to query the job execution data.

#### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: Download a CSV file.

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

#### Column List

Legend

| Column          | Data Type            | Р | M | F | DV |
|-----------------|----------------------|---|---|---|----|
| JOB_ID          | VARCHAR2(64<br>CHAR) | X | X |   |    |
| WORKFLOW_TYP    | VARCHAR2(32<br>CHAR) | X | X |   |    |
| JOB_NAME        | VARCHAR2(32<br>CHAR) |   |   |   |    |
| JOB_VERSION     | VARCHAR2(32<br>CHAR) |   |   |   |    |
| LOCAL_START_TII | MEIMESTAMP(3)        |   |   |   |    |
| LOCAL_END_TIME  | TIMESTAMP(3)         |   |   |   |    |
| GMT_START_TIME  | TIMESTAMP(3)         |   |   |   |    |
| GMT_END_TIME    | TIMESTAMP(3)         |   |   |   |    |
| DURATION        | NUMBER(10)           |   |   |   |    |
| STATUS          | VARCHAR2(32<br>CHAR) |   |   |   |    |
| CREATED_TS      | NUMBER(10)           |   | X |   |    |

#### JOB\_ID

ID that uniquely identifies the execution instance of the job.

#### WORKFLOW\_TYPE

The name of the step of the job, such as Outbound.

#### JOB NAME

The name of the job, such as Job\_ExtractICON.

#### JOB\_VERSION

The version of the job, such as 8.1.000.10.

#### LOCAL\_START\_TIME

The date and time the first step of the job started (in the time zone where Genesys Info Mart Server is running).

**Note:** Because the Genesys Info Mart Server always runs in the GMT time zone, the value of this field is always the same as GMT\_START\_TIME.

#### LOCAL\_END\_TIME

The date and time the last step of the job ended (in the time zone where Genesys Info Mart Server is running).

**Note:** Because the Genesys Info Mart Server always runs in the GMT time zone, the value of this field is always the same as GMT END TIME.

#### GMT\_START\_TIME

The date and time the first step of the job started (in GMT time zone).

#### **GMT\_END\_TIME**

The date and time the last step of the job ended (in GMT time zone).

#### **DURATION**

The duration of the job, in seconds.

#### **STATUS**

The status of the job, such as COMPLETE or FAILED.

#### CREATED\_TS

The UTC-equivalent value of the date and time at which the job started.

#### Index List

| CODE          | U | С | Description                 |
|---------------|---|---|-----------------------------|
| I_C_ETL_H_CTS |   |   | Improves purge performance. |

#### Index I\_C\_ETL\_H\_CTS

| Field      | Sort      | Comment |
|------------|-----------|---------|
| CREATED_TS | Ascending |         |

## Subject Areas

No subject area information available.