



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Info Mart Physical Data Model for an Oracle Database

Table [RECORD\\_FIELD\\_GROUP\\_2](#)

## Table RECORD\_FIELD\_GROUP\_2

### Description

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type for the RECORD\_FIELD\_2\_STRING\_1 Through RECORD\_FIELD\_2\_STRING\_10 columns modified in single-language databases); 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is not partitioned.

This table allows contact attempt facts to be described by deployment-specific field values of outbound campaign calling lists. Each row describes a distinct combination of calling list field values. A new row is issued for each distinct combination of calling list field values that are encountered in the contact attempt source data. Calling list field values must be of low cardinality, to prevent this dimension from becoming as large as the fact tables.

#### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

### Column List

#### Legend

Column	Data Type	P	M	F	DV
RECORD_FIELD_GROUP_KEY	NUMBER(10)	X	X		
TENANT_KEY	NUMBER(10)		X	X	

Table RECORD\_FIELD\_GROUP\_2

Column	Data Type	P	M	F	DV
CREATE_AUDIT_KEY	NUMBER(19)		X	X	
RECORD_FIELD_2_STRING_1 Through RECORD_FIELD_2_STRING_10	VARCHAR2(255 CHAR)				
PURGE_FLAG	NUMBER(1)				

## RECORD\_FIELD\_GROUP\_2\_KEY

The primary key of this table and the surrogate key that is used to join this dimension table to the fact tables.

## TENANT\_KEY

The surrogate key that is used to join the TENANT dimension to the fact tables.

## CREATE\_AUDIT\_KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools—that is, applications that need to identify newly added data.

## RECORD\_FIELD\_2\_STRING\_1 Through RECORD\_FIELD\_2\_STRING\_10

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type changed from varchar to nvarchar in single-language databases)

The text string value number one through ten, respectively, of a custom record field.

## PURGE\_FLAG

This field is reserved.

## Index List

No indexes are defined.

## Subject Areas

- **Contact\_Attempt** — Represents outbound campaign contact record attempts. An attempt may or may not include dialing.