

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Info Mart Physical Data Model for an Oracle Database

Table RESOURCE ANNEX

# Table RESOURCE\_ANNEX

# Description

**Modified:** 8.5.015.19 (PRODUCER\_BATCH\_ID added); 8.5.014.34 (in Microsoft SQL Server, data type for the VALUE column modified in single-language databases and for the SECTIONNAME and KEYNAME columns modified in single- and multi-language databases); 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is not partitioned.

This table stores additional configuration data for configuration objects of type Person.

The data is based on the records for these configuration objects that are stored in the GC\_ANNEX table of the configuration IDB. Genesys Interactive Insights uses the data associated with Person configuration objects to control visibility for certain data and reports.

A new row is issued for each configuration option specified in an **RPT\*** section (in other words, in a configuration section with section name starting with "RPT") on the Annex tab of the corresponding configuration object. Changing the name of the specified option causes a new row to be created. Changing the name of the specified section causes a new row to be created for each option that is associated with this section. Deleting the section causes all records for associated options to be terminated.

## Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: Download a CSV file.

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

# Column List

#### Legend

Column	Data Type	Р	M	F	DV
RESOURCE_KEY	NUMBER(10)	X	X	X	
TENANT_KEY	NUMBER(10)		X	X	
SECTIONNAME	VARCHAR2(255 CHAR)	X	X		
KEYNAME	VARCHAR2(255 CHAR)	X	X		
VALUE	VARCHAR2(255 CHAR)				
END_TS	NUMBER(10)		X		
CFGOBJECTID	NUMBER(10)		X		
CFGOBJECTTYPE	NUMBER(3)		X		
CREATE_AUDIT_k	(ENUMBER(19)		X	X	
UPDATE_AUDIT_k	(ENUMBER(19)		X	X	
ACTIVE_FLAG	NUMBER(1)		X		
PRODUCER_BATC	HNUMBER(19)				

#### RESOURCE KEY

The primary key that is used to join this table to the RESOURCE dimension.

#### TENANT KEY

The surrogate key that is used to join this dimension to the TENANT dimension.

#### **SECTIONNAME**

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type changed from varchar to nvarchar in single-language databases and the size of the nvarchar data type changed in multi-language databases)

The name of the configuration section on the Annex tab of the configuration object in which the specified option is located. This value equals the value of the GC\_ANNEX.SECTIONNAME IDB field for a respective DN, Person, or Switch record.

#### **KEYNAME**

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type changed from varchar to nvarchar in single-language databases and the size of the nvarchar data type changed in multi-language

#### databases)

The name of the configuration option that is set on the Annex tab of the configuration object. If the object type is Person, the option specifies the geographical location, business line, or organization structure. This value equals the value of the GC\_ANNEX.KEYNAME field in IDB for a respective DN, Person, or Switch record.

#### **VALUE**

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type changed from varchar to nvarchar in single-language databases)

The value of the configuration option that is set on the Annex tab of the configuration object. This value equals the value of the GC\_ANNEX.VALUE field in IDB for a respective DN, Person, or Switch record.

#### END\_TS

The UTC-equivalent value of the date and time at which the configuration was changed (for example, the option, section, or object was removed). This value equals the value of the GC\_ANNEX.DELETED field in IDB for a respective DN, Person, or Switch record.

#### **CFGOBJECTID**

The DBID of the configuration object. This value equals the value of the GC\_ANNEX.CFGOBJECTID field in IDB for a respective DN, Person, or Switch record.

#### **CFGOBJECTTYPE**

The type of the configuration object. This value equals the value of the GC\_ANNEX.CFGOBJECTTYPE field in IDB for a respective DN, Person, or Switch record.

#### CREATE AUDIT KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools—that is, applications that need to identify newly added data.

#### UPDATE AUDIT KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools—that is, applications that need to identify recently modified data.

### ACTIVE FLAG

Indicates whether the specified configuration option is currently active: 0 = No, 1 = Yes.

# PRODUCER\_BATCH\_ID

Introduced: Release 8.5.015.19

Reserved for internal use.

# Index List

CODE	U	С	Description
I_RESOURCE_ANNEX	X		Improves access time, based on dimension values.
I_RESOURCE_ANNEX_END	_TS		Improves access time, based on the End Timestamp.

# Index I\_RESOURCE\_ANNEX

Field	Sort	Comment
CFGOBJECTID	Ascending	
CFGOBJECTTYPE	Ascending	
KEYNAME	Ascending	
SECTIONNAME	Ascending	

# Index I\_RESOURCE\_ANNEX\_END\_TS

Field	Sort	Comment
END_TS	Ascending	

# Subject Areas

No subject area information available.