

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Info Mart Physical Data Model for a Microsoft SQL Server Database

Table CTL EXTRACT HISTORY

# Table CTL\_EXTRACT\_HISTORY

# Description

**Modified:** 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is partitioned.

This table contains information about the last attempted and last successful incremental extraction. The UTC-equivalent value of the date and time and/or a sequence number are provided for the data source table that was used in the last extract attempt. Data source information covers such details as the IDB from which the data was extracted, the ICON instance that populated the IDB, and the application that was the original source of data (T-Server, Outbound Contact Server, and so forth).

#### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: Download a CSV file.

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

# Column List

#### Legend

Column	Data Type	P	M	F	DV
TABLE_NAME	varchar(255)		X		
DATA_SOURCE_KEYnt		X			
DATA_SOURCE_TYPEE					

Column	Data Type	Р	M	F	DV
ROW_COUNT	int				
MAX_TIME	datetime				
MAX_TS	int				
ICON_DBID	int		Χ		0
DSS_ID	int				
PROVIDERTAG	int				
EXTRACT_START_	Tdlatetime				
EXTRACT_END_TIMEatetime					
JOB_ID	varchar(64)		X		
JOB_NAME	varchar(32)				
JOB_VERSION	varchar(64)				
DAP_NAME	varchar(255)/nva	archar(255)			
CREATE_AUDIT_k	(E <b>Y</b> umeric(19)		X	X	
CREATED_TS	int		X		

## TABLE\_NAME

The name of the IDB table from which data was extracted.

# DATA\_SOURCE\_KEY

The surrogate key that is used to join this table to the CTL\_DS table.

# DATA SOURCE TYPE

The type of the data source server as reported by ICON. This field is set to one of the following values:

- 1 T-Server
- 2 Interaction Server
- 3 OCS Server
- 4 Configuration Server

## **ROW\_COUNT**

The number of records that are extracted in a given extraction cycle.

#### MAX TIME

The date and time, in the Genesys Info Mart server time zone, that represent the highest timestamp value for the records that are extracted in a given extraction cycle.

#### MAX TS

The UTC-equivalent value of the date and time that represents the highest timestamp value for the records that are extracted in a given extraction cycle.

#### ICON DBID

ID that uniquely identifies the ICON application instance. The value is the same as the one that ICON provided in the IDB.

#### DSS ID

The data source session identifier that is used in a given extraction cycle.

#### **PROVIDERTAG**

The ID of the ICON provider class, such as 5 for the configuration information provider (cfg). This field is reserved.

#### EXTRACT\_START\_TIME

The date and time when the extraction job started.

# EXTRACT\_END\_TIME

The date and time when the extraction job finished.

#### JOB ID

ID that uniquely identifies the execution instance of the job.

#### JOB NAME

The name of the job that extracted data--for example, Job\_ExtractICON.

## JOB\_VERSION

The version of the job that extracted data--for example, 8.1.000.10.

#### DAP NAME

The name of the Database Access Point (DAP) through which data was extracted.

#### CREATE AUDIT KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools--that is, applications that need to identify newly added data.

#### CREATED TS

The UTC-equivalent value of the date and time at which the extraction job started.

#### Index List

CODE	U	С	Description
I_C_EXTRACT_H_CTS			Improves purge performance.

# Index I\_C\_EXTRACT\_H\_CTS

Field	Sort	Comment
CREATED_TS	Ascending	

# Subject Areas

No subject area information available.