



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## Genesys Info Mart Physical Data Model for an Oracle Database

Table **CAMPAIGN\_GROUP\_STATE**

# Table CAMPAIGN\_GROUP\_STATE

## Description

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type for the CAMPAIGN\_GROUP\_STATE and CAMPAIGN\_GROUP\_STATE\_CODE columns modified in single-language databases); 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is not partitioned.

Allows facts to be described based on attributes of an outbound campaign group status. Each row describes one campaign group status. Rows exist for the Loaded, Started, and Unloading statuses.

### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

## Column List

### Legend

Column	Data Type	P	M	F	DV
CAMPAIGN_GROUP_STATE_ID	NUMBER(10)	X	X		
CAMPAIGN_GROUP_STATE	VARCHAR2(32 CHAR)				
CAMPAIGN_GROUP_STATE_CODE	VARCHAR2(32 CHAR)				

Table CAMPAIGN\_GROUP\_STATE

---

Column	Data Type	P	M	F	DV
CREATE_AUDIT_KEY	NUMBER(19)		X	X	
UPDATE_AUDIT_KEY	NUMBER(19)		X	X	

## CAMPAIGN\_GROUP\_STATE\_KEY

The primary key of this table and the surrogate key that is used to join this dimension table to the fact tables.

## CAMPAIGN\_GROUP\_STATE

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type changed from varchar to nvarchar in single-language databases)

The campaign group session state. This field is set to one of the following values:

- Null
- Loaded
- Started
- Unloading

This value can change with localization.

## CAMPAIGN\_GROUP\_STATE\_CODE

**Modified:** 8.5.014.34 (in Microsoft SQL Server, data type changed from varchar to nvarchar in single-language databases)

The code for the campaign group session state. This field is set to one of the following values:

- NULL
- LOADED
- STARTED
- UNLOADING

This value does not change with localization.

## CREATE\_AUDIT\_KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools — that is, applications that need to identify newly added data.

## UPDATE\_AUDIT\_KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools — that is, applications that need to identify recently modified data.

## Index List

No indexes are defined.

## Subject Areas

- **Campaign\_Group\_State** — Represents campaign groups from the perspective of states they go through, such as "Loaded", "Started", and "Unloading".