



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Mobile Services API Reference

Stat Service API

---

## Contents

- 1 Stat Service API
  - 1.1 Stat Request APIs
  - 1.2 Extended Stat Request API
  - 1.3 EWT APIs
  - 1.4 Configuration
  - 1.5 Subscribe to Statistic Server Event Notifications

# Stat Service API

This API retrieves statistics from the Genesys Statistics Server (Stat Server) and URS.

## Important


You need an Authentication header for this service.

Stat Request APIs

Sequence Diagrams


**[+] Show Peek Stat Sequence (Statistic is not already opened)**


### PeekStat Sequence (Statistic not already opened)



### [+] Show Peek Stat Sequence (Statistic already exists)

## PeekStat Sequence (Statistic already exist)



**[+] Show Peek Stat Sequence (Update Cache)**

### Accessing the APIs

The Stat Server API exposes two interfaces:

- **"genesys/1/internal\_statistic"** — for internal access with no authentication control.
- **"genesys/1/statistic"** — for external use, which uses Basic Access Authentication (BA) to authenticate users.

As a standard protocol, the username and password for BA can be passed in the URL, as shown here:

```
http://username:password@127.0.0.1:8080/genesys/1/statistic
```

This API provides the following queries:

- **PeekStat**
- **URS Stat**

#### Important

See the **Extended API** to query multiple statistics.

### PeekStat Request

This request fetches one statistic value.

Operation

| Method    | POST                 |           |             |
|-----------|----------------------|-----------|-------------|
| URL       | /genesys/1/statistic |           |             |
| Parameter | Type                 | Mandatory | Description |



| Method                                                                                                                | POST                |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------|---------------------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Header Parameters                                                                                                     |                     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Cache-Control : max-age=XX                                                                                            | A number of seconds | no  | The max-age value used to check if GMS has to recalculate the statistic. If the peek statistic time window is greater than max-age, GMS recalculates the statistic value. If the value is not present, it returns the latest value in cache.                                                                                                                                                                                                                                                 |
| Body                                                                                                                  |                     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| objectId, objectType, tenant, metric (or statisticType), filter, notificationMode, timeProfile, timeRange, timeRange2 |                     | yes | <p>The body can be either a MultiPart form or an x-www-form-urlencoded form consisting of different items representing the key/value pairs associated with the statistic (objectId, objectType, tenant, tenantPassword, metric, notificationMode, filter, timeProfile, timeRange, timeRange2).</p> <ul style="list-style-type: none"><li>NotificationMode can be NoNotification, Reset, or Immediate.</li><li>filter is the business attribute value to use to filter the results.</li></ul> |

## Response

| HTTP code    | 200                                               |
|--------------|---------------------------------------------------|
| HTTP Message | OK                                                |
| HTTP Header  | Content-Type: application/json;charset=UTF-8      |
| Body         | A JSON object representing a structure with value |

If a problem occurs during operation, the following status codes are returned:

| HTTP code | HTTP Message | HTTP Body                                                                                                                            |
|-----------|--------------|--------------------------------------------------------------------------------------------------------------------------------------|
| 400       | Bad Request  | message: {"message":"Notification Mode is unknown","exception":"com.genesyslab.gsg.services.statistic.StatSer                        |
| 401       | Unauthorized | Access to API refused                                                                                                                |
| 403       | Forbidden    | message: {"message":"Object type not valid","exception":"com.genesyslab.gsg.services.statistic.StatSer                               |
| 403       | Forbidden    | message: {"message":"Agent 'Kippola' (Tenant 'Environment') not found","exception":"com.genesyslab.gsg.services.statistic.StatSer    |
| 403       | Forbidden    | message: {"message":"Wrong parameter","exception":null}                                                                              |
| 500       | Server Error | message: {"message":"Metric (TotalLoginTime;) not found on running StatServer","exception":"com.genesyslab.gsg.services.statistic.St |
| 500       | Server Error | message: {"message":"Statistic Service bad parameter for tenant","exception":"com.genesyslab.gsg.services.statistic.StatSe           |

### Important

You can make this request without using authentication by replacing **/genesys/1/statistic** with **/genesys/1/internal\_statistic**.

### Example

#### Request

```
$ curl -v -u default:password -X POST --data "metric=TotalLoginTime&objectType=Agent&objectId=KSippola&tenant=Environment"
http://localhost:8080/genesys/1/statistic
Content-Type: application/x-www-form-urlencoded
```

#### Response

```
HTTP/1.1 200 OK
Content-Type: application/json; charset=UTF-8
{"value":4963}
```

### URS Stat Request

This API allows you to query URS statistics with GMS.

To use this request, you must add the following configuration information:

- URS version must be 8.1.400.12 or higher.
- In your URS application, allow HTTP requests:
  1. Open your URS application in Genesys Administrator or Configuration Manager.
  2. In the Server Info tab, create an HTTP listening port.
- In the reporting section of your GMS application, create the `_urs_url` option and set it to the URL of URS.

You can also create a **builtin** service to retrieve URS statistics with the `urs-stat` template. When you create your service, select the "urs-stat" type in the Admin UI service panel. See the [Admin UI Help](#) for further details. Then, to retrieve the statistics, you can make the following request:

```
GET http://<gms_home>:<gms_port>/genesys/1/service/<urs_service>
```

## Operation

| Method                     | GET                                         |           |                                                                                                                                                                                                                                              |
|----------------------------|---------------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URL                        | /genesys/1/statistic/urs/ <i>parameters</i> |           |                                                                                                                                                                                                                                              |
| Parameter                  | Type                                        | Mandatory | Description                                                                                                                                                                                                                                  |
| <b>Header Parameters</b>   |                                             |           |                                                                                                                                                                                                                                              |
| Cache-Control : max-age=XX | A number of seconds                         | no        | The max-age value used to check if GMS has to recalculate the statistic. If the peek statistic time window is greater than max-age, GMS recalculates the statistic value. If the value is not present, it returns the latest value in cache. |
| <b>URL Parameters</b>      |                                             |           |                                                                                                                                                                                                                                              |
| parameters                 |                                             | no        | For information on these parameters, either refer to the <a href="#">URS documentation</a> or send the following HTTP request to URS:<br>http://URS_host:URS_HTTP_port/urs/help/                                                             |

## Response

| HTTP code    | 200                                               |
|--------------|---------------------------------------------------|
| HTTP Message | OK                                                |
| HTTP Header  | Content-Type: application/json;charset=UTF-8      |
| Body         | A JSON object representing a structure with value |

If a problem occurs during operation, the following status codes are returned:

---

| HTTP code | HTTP Message | HTTP Body                                                                         |
|-----------|--------------|-----------------------------------------------------------------------------------|
| 401       | Unauthorized | message: "Authentication failed: username and/or password is incorrect"           |
| 500       | Server error | message: {"message":"Wrong request","exception":"org.apache.http.HttpException"}  |
| 500       | Server error | message: {"message":"Call not found","exception":"org.apache.http.HttpException"} |

**Note:** You can make this request without using authentication by replacing **/genesys/1/statistic/urs/** with **/genesys/1/internal\_statistic/urs/**.

### Example

#### Request

```
$ curl -v -u default:password "http://localhost:8080/genesys/1/statistic/urs/stat/targetstate?tenant=Environment◇=KSippola.A&json=&ext="
```

#### Response

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "dnsall":6,
  "voice":1,
  "status":4,
  "loading":0,
  "dns":
  [
    {
      "type":38,
      "number":"KSippola",
      "switch":"",
      "status":4,
      "loading":0,
      "ready":1,
      "media":1,
      "loggedin":0
    },
  ],
}
```

```
{
  "type":36,
  "number":"KSippola",
  "switch":"",
  "status":2,
  "loading":0,
  "ready":0,
  "media":1,
  "loggedin":0
},
{
  "type":61,
  "number":"KSippola",
  "switch":"",
  "status":4,
  "loading":0,
  "ready":1,
  "media":1,
  "loggedin":0
},
{
  "type":1,
  "number":"7001",
  "switch":"SIP_Switch",
  "status":4,
  "loading":0,
  "ready":1,
  "media":0,
  "loggedin":0
},
{
  "type":1,
  "number":"7001_IM",
  "switch":"SIP_Switch",
  "status":8,
  "loading":0,
  "ready":0,
  "media":0,
  "loggedin":0
},
{
  "type":38,
  "number":"7001_IM",
```

```
        "switch": "SIP_Switch",
        "status": 8,
        "loading": 0,
        "ready": 0,
        "media": 0,
        "loggedin": 0
    },
    "login": "SIP1",
    "place": "SIP_Server_Placel",
    "ready": 1,
    "agent": "KSippola",
    "dnsrdy": 3
}
```

## Extended Stat Request API

- **PeekStat Request: Retrieve configured statistics**
- **PeekStat Request: Querying Multiple Statistic Values in a Single Request (V1)**
- **PeekStat Request: Querying Multiple Statistic Values in a Single Request (V3)**
- **PeekStat Request: Filtering Multiple Statistic Values in a Single Request**

### PeekStat Request: Retrieve configured statistics

Starting with 8.5.101, you can provision statistics in the **stat** **section** of your configuration options instead of passing properties as parameters of the statistics requests.

For instance, you can define **stat1** in your configuration as follows:

```
[stat.stat1]
_type=builtin
_service=statistic
```

```
metric=TotalLoginTime
notificationMode=Immediate
objectId=KSippola
objectType=Agent
tenant=Environment
filter=Bronze
```

Then, you can retrieve the statistics for stat1 with a simple statistics query:

```
POST http://localhost:8080/genesys/1/statistic/stat1
```

Response:

```
{"value":41889}
```

## Operation

| Method                                                           | POST                                   |           |                                                                                                                                                                                                                         |
|------------------------------------------------------------------|----------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URL                                                              | /genesys/1/statistic/ <b>stat_name</b> |           |                                                                                                                                                                                                                         |
| Parameter                                                        | Type                                   | Mandatory | Description                                                                                                                                                                                                             |
| <b>Header</b>                                                    |                                        |           |                                                                                                                                                                                                                         |
| Cache-Control: max-age                                           | Integer                                | no        | The max-age value in seconds of the statistic. If the peek statistic time window is greater than max-age, GMS recalculates the statistic value. If max-age is not specified, GMS returns the latest value in the cache. |
| <b>URL parameters</b>                                            |                                        |           |                                                                                                                                                                                                                         |
| stat_name                                                        | String                                 | yes       | Name of the statistic defined in the stat section of your configuration.                                                                                                                                                |
| <b>Body</b>                                                      |                                        |           |                                                                                                                                                                                                                         |
| objectId, objectType, tenant, metric (or statisticType), filter, |                                        | yes       | The body can be either a MultiPart form or an x-www-form-urlencoded                                                                                                                                                     |



| Method                                               | POST |  |                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------------------------------------|------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| notificationMode, timeProfile, timeRange, timeRange2 |      |  | <p>form consisting of different items representing the key/value pairs associated with the statistic (objectId, objectType, tenant, tenantPassword, metric, notificationMode, filter, timeProfile, timeRange, timeRange2).</p> <ul style="list-style-type: none"><li>• NotificationMode can be NoNotification, Reset, or Immediate.</li><li>• filter is the business attribute value to use to filter the results.</li></ul> |

## Response

|              |                                              |
|--------------|----------------------------------------------|
| HTTP code    | 200                                          |
| HTTP Message | OK                                           |
| HTTP Header  | Content-Type: application/json;charset=UTF-8 |
| Body         | A JSON object representing the statistic.    |

If a problem occurs during operation the following status codes are returned:

| HTTP code | HTTP message | Body                                                                                                                    |
|-----------|--------------|-------------------------------------------------------------------------------------------------------------------------|
| 400       | Bad request  | message: {"message":"stat.total-time not found","exception":"com.genesyslab.gsg.services.context"}<br>check GMS options |
| 401       | Unauthorized | Access to API refused                                                                                                   |

## PeekStat Request: Querying Multiple Statistic Values in a Single Request

### Important

Starting with 8.5.216, this query is available in **V3**, which fixes some issues that happened when some object types were removed.

This request gets the current values of several peek statistic objects.

### Operation

| Method                                                                                                                | POST                  |           |                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URL                                                                                                                   | /genesys/1/statistics |           |                                                                                                                                                                                                                                                                                                                                                                                              |
| Parameter                                                                                                             | Type                  | Mandatory | Description                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Body</b>                                                                                                           |                       |           |                                                                                                                                                                                                                                                                                                                                                                                              |
| objectId, objectType, tenant, metric (or statisticType), filter, notificationMode, timeProfile, timeRange, timeRange2 |                       | yes       | <p>The body can be either a MultiPart form, an x-www-form-urlencoded form, or a JSON object consisting of different items representing the key/value pairs associated with the statistic (objectId, objectType, tenant, tenantPassword, metric, notificationMode, filter, timeProfile, timeRange, timeRange2).</p> <ul style="list-style-type: none"><li>• NotificationMode can be</li></ul> |

---

| Method | POST |  |                                                                                                                                                                  |
|--------|------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        |      |  | <p>NoNotification, Reset, or Immediate.</p> <ul style="list-style-type: none"><li>filter is the business attribute value to use to filter the results.</li></ul> |

## Response

| HTTP code    | 200                                               |
|--------------|---------------------------------------------------|
| HTTP Message | OK                                                |
| HTTP Header  | Content-Type: application/json;charset=UTF-8      |
| Body         | A JSON object representing a structure with value |

If a problem occurs during an operation the following status codes are returned:

| HTTP code | HTTP message | Body                                                                                                                                                                                                                                                                                                                                           |
|-----------|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 200       | OK           | <p>You get an error message instead of one of the expected values if the requested statistic is incorrect; for example: message: {"stat1":8940,"stat2":"do not have 5 semicolon delimiters"}</p> <p>This means that, instead of getting a 400 Bad request response, you are able to retrieve statistics, even if one of them is incorrect.</p> |
| 400       | Bad request  | message: message: {"message":"Error for stat1: Agent 'Kippola' (Tenant 'Environment') not found","exception":"com.genesyslab.gsg.services.statist                                                                                                                                                                                              |
| 401       | Unauthorized | Access to API refused                                                                                                                                                                                                                                                                                                                          |

---

| HTTP code | HTTP message | Body                                                                                                                                |
|-----------|--------------|-------------------------------------------------------------------------------------------------------------------------------------|
| 403       | Forbidden    | message: {"message": "Wrong parameter", "exception": null}                                                                          |
| 500       | Server Error | message: {"message": "Metric (CurrentGrouargetState) not found on running StatServer", "exception": "com.genesyslab.gsg.services.st |

### Important

You can make this request without using authentication by replacing **/genesys/1/statistics** with **/genesys/1/internal\_statistics**.

## Examples with Multiple Statistics

The following example uses application/x-www-form-urlencoded:

### Request

```
$ curl -v -u default:password -X POST --data  
"stat1=TotalLoginTime;Agent;KSippola;Environment;Immediate;&stat2=CurrentGroupTargetState;GroupAgents;Billing;Environment;Immediate;Silver"  
http://localhost:8080/genesys/1/statistics
```

Content-Type: application/x-www-form-urlencoded

### Response

```
HTTP/1.1 200 OK  
Content-Type: application/json; charset=UTF-8  
{  
  "stat1": 248,  
  "stat2":  
  [
```

```
{
  "agentDbId":102,
  "placeDbId":102,
  "agentId":"KSippola",
  "placeId":"SIP_Server_Place1",
  "extensions":
  [
    {"VOICE_MEDIA_STATUS":4},
    {"AGENT_VOICE_MEDIA_STATUS":4},
    {"DEVCAP":"AAIAAAAAAAEABXZvaWNlAAAAAAAAAAAAABVxTnEgAAAAAAQAAAAIABXZvaWNlAAAAAAAAAAAAAAVxTnEgAEY2hhdAAAAAAAAAD/
AAAAAFcU5xIAAAAA"}
  ],
  "mediaCapacityList":
  [
    {"mediaType":"chat",
      "currentInteractions":0,
      "maxInteractions":1,
      "currentMargin":1,
      "timestamp":1460961964},
    {"mediaType":"vmail",
      "currentInteractions":0,
      "maxInteractions":0,
      "currentMargin":0,
      "timestamp":1460554482},
    {"mediaType":"voice",
      "currentInteractions":0,
      "maxInteractions":1,
      "currentMargin":1,
      "timestamp":1460961964},
    {"mediaType":"webcallback",
      "currentInteractions":0,
      "maxInteractions":1,
      "currentMargin":1,
      "timestamp":1460961964}
  ],
  "dnstatusExList":
  [
    {"dnId":"7001",
      "gswDnTypes":1,
      "mediaCapacityList":
      [
        {"mediaType":"voice",
          "currentInteractions":0,
```

```
        "maxInteractions":1,
        "currentMargin":1,
        "timestamp":1460987666}
    ],
    "multimedia":0,
    "status":4,
    "switchId":"SIP_Switch",
    "time":1460554482},
{"dnId":"7001_IM",
 "gswDnTypes":1,
 "mediaCapacityList":
 [
     {"mediaType":"voice",
      "currentInteractions":0,
      "maxInteractions":0,
      "currentMargin":0,
      "timestamp":1460987666},
     {"mediaType":"chat",
      "currentInteractions":0,
      "maxInteractions":255,
      "currentMargin":0,
      "timestamp":1460987666}
 ],
 "multimedia":1,
 "status":8,
 "switchId":"SIP_Switch",
 "time":1460553961}
    ]
}
}
```

The following example uses JSON:

### Request

```
$ curl -v -u default:password -H "Content-Type: application/json" -X POST --data
'{"stat1":{"objectId":"KSippola","objectType":"Agent","tenant":"Environment","tenantPassword":"","metric":"TotalLoginTime","filter":"","notificationMode":"Imr
http://localhost:8080/genesys/1/statistics

Content-Type: application/json
```

## Response

HTTP/1.1 200 OK

Content-Type: application/json; charset=UTF-8

```
{
  "stat1":3426,
  "stat3":
  [
    {
      "agentDbId":102,
      "placeDbId":102,
      "agentId":"KSippola",
      "placeId":"SIP_Server_Place1",
      "extensions":
      [
        {"VOICE_MEDIA_STATUS":4},
        {"AGENT_VOICE_MEDIA_STATUS":4},
        {"DEVCAP":"AAIAAAAAAEABXZvaWNlAAAAAAAAAAAAEAAAABVxTzkwAAAAAAQAAAAIABXZvaWNlAAAAAAAAAAAAAVxTzkwAEY2hhdAAAAAAAAAD/AAAAAFcU85MAAAAA"}
      ],
      "mediaCapacityList":
      [
        {
          "mediaType":"chat",
          "currentInteractions":0,
          "maxInteractions":1,
          "currentMargin":1,
          "timestamp":1460961964},
        {
          "mediaType":"vmail",
          "currentInteractions":0,
          "maxInteractions":0,
          "currentMargin":0,
          "timestamp":1460554482},
        {
          "mediaType":"voice",
          "currentInteractions":0,
          "maxInteractions":1,
          "currentMargin":1,
          "timestamp":1460961964},
        {
          "mediaType":"webcallback",
          "currentInteractions":0,
          "maxInteractions":1,
          "currentMargin":1,

```

```
        "timestamp":1460961964}
    ],
    "dnstatusExList":
    [
        {
            "dnId":"7001",
            "gswDnTypes":1,
            "mediaCapacityList":
            [
                {
                    "mediaType":"voice",
                    "currentInteractions":0,
                    "maxInteractions":1,
                    "currentMargin":1,
                    "timestamp":1460990867}
            ],
            "multimedia":0,
            "status":4,
            "switchId":"SIP_Switch",
            "time":1460554482},
        {
            "dnId":"7001_IM",
            "gswDnTypes":1,
            "mediaCapacityList":
            [
                {
                    "mediaType":"voice",
                    "currentInteractions":0,
                    "maxInteractions":0,
                    "currentMargin":0,
                    "timestamp":1460990867},
                {
                    "mediaType":"chat",
                    "currentInteractions":0,
                    "maxInteractions":255,
                    "currentMargin":0,
                    "timestamp":1460990867}
            ],
            "multimedia":1,
            "status":8,
            "switchId":"SIP_Switch",
            "time":1460553961}
        ]
    ]
}
```



## PeekStat Request: Filtering Multiple Statistic Values in a Single Request

### Important

This is a JSON query. This JSON query is available since 8.5.004.05.

### Operation

| Method                                                                                                                                                                                           | POST                  |           |             |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------|-------------|
| URL                                                                                                                                                                                              | /genesys/1/statistics |           |             |
| Parameter                                                                                                                                                                                        | Type                  | Mandatory | Description |
| <b>Body:</b> A JSON item representing the key/value pairs associated with statistics (objectId, objectType, tenant, tenantPassword, metric, notificationMode, filter).                           |                       |           |             |
| <ul style="list-style-type: none"><li>filter is the business attribute value to use to filter the results.</li><li>notificationMode can be set to NoNotification, Reset, or Immediate.</li></ul> |                       |           |             |

### Response

| HTTP code    | 200                                                                                                       |
|--------------|-----------------------------------------------------------------------------------------------------------|
| HTTP Message | OK                                                                                                        |
| HTTP Header  | Age: containing the age (in seconds) of the statistic value.                                              |
| Body         | A JSON array of key/value pairs where key is the key stat (see request) and value is the statistic value. |

If a problem occurs during subscription, the following status codes are returned:

---

| HTTP code | HTTP Message          | HTTP Body                                                                                                                                                                             |
|-----------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 400       | Bad Request           | The provided filter is incorrect; for example:<br>{"message":"Filter name is not found","exception":"com.genesyslab.gsg.services.statistic"}.                                         |
| 403       | Forbidden             | Part of the submitted data is incorrect, for example:<br>{"message":"Place 'SIP_Server_Place' (Tenant 'Environment') not found","exception":"com.genesyslab.gsg.services.statistic"}. |
| 500       | Internal server error | If Stat Server is not connected, it returns, for example,<br>{"message":"Statistic Service unavailable","exception":"com.genesyslab.gsg.services.statistic"}.                         |

### Example with Filter

#### Query

http://localhost:8080/genesys/1/statistics

Input: JSON File

```
{
  "stat1": {
    "objectId": "KSippola",
    "objectType": "Agent",
    "tenant": "Environment",
    "tenantPassword": "",
    "metric": "TotalLoginTime",
    "filter": "Bronze"
  },
  "stat2": {
```

```
{
  "objectId": "9002@SIP_Switch",
  "objectType": "Queue",
  "tenant": "Environment",
  "metric": "ExpectedWaitTime"
}
```

### Response

```
HTTP/1.1 200 OK
Date: Thu, 19 Jun 2014 09:06:43 GMT
Content-Type: application/json; charset=UTF-8
Content-Type: application/json
Content-Length: 25

{"stat1":0,"stat2":10000}
```

## PeekStat Request: Querying Multiple Statistic Values in a Single Request (V3)

### Added in 8.5.216

This request gets multiple statistic values from several statistics and replaces the former V1 query (see [the description above](#)).

In V1, if one statistic object type no longer exists in the system, the query of multiple statistics containing one of these removed object types will fail, even if other queried object types exist. Using V3, when subscribing to several statistics, the operation will not stop on the first statistic item that fails, for example, if the given statistic does not exist.

### Important

In V3, even if the query is similar to V1, the object response is formatted differently. See below for further details.

## Operation

| Method                                                                                                                | POST                  |           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------|-----------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URL                                                                                                                   | /genesys/3/statistics |           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Parameter                                                                                                             | Type                  | Mandatory | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Body</b>                                                                                                           |                       |           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| objectId, objectType, tenant, metric (or statisticType), filter, notificationMode, timeProfile, timeRange, timeRange2 |                       | yes       | <p>The body can be either a MultiPart form, an x-www-form-urlencoded form, or a JSON object consisting of different items representing the key/value pairs associated with the statistic (objectId, objectType, tenant, tenantPassword, metric, notificationMode, filter, timeProfile, timeRange, timeRange2).</p> <ul style="list-style-type: none"><li>NotificationMode can be NoNotification, Reset, or Immediate.</li><li>filter is the business attribute value to use to filter the results.</li></ul> |

## Response

| HTTP code    | 200                                                                                                                |
|--------------|--------------------------------------------------------------------------------------------------------------------|
| HTTP Message | OK                                                                                                                 |
| HTTP Header  | Content-Type: application/json;charset=UTF-8                                                                       |
| Body         | <p>A JSON object representing a structure with a status and a value for each requested statistic.</p> <pre>{</pre> |

| HTTP code | 200                                                                                                                                                                        |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <pre>"statId": { "status": "&lt;ok or error &gt;",             "value": &lt;value or error message if status =             error &gt; },             ...           }</pre> |

If a problem occurs during operation the following status codes are returned:

| HTTP code | HTTP message | Body                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 200       | OK           | <p>The statistics</p> <p>Check the status of each stat object. You get an error message instead of one of the expected values if the requested statistic is incorrect; for example:</p> <pre>{ "stat2": { "status": "ok", "value": 0 }, "stat1": { "status": "error", "value": "Agents Group fakeAG (Tenant Environment) not found" } }</pre> <p>It means that, instead of getting a 400 Bad request response, you are able to retrieve statistics, even if one of them is incorrect.</p> |
| 401       | Unauthorized | Access to API refused                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 403       | Forbidden    | <pre>message: {"message": "Wrong parameter", "exception": null}</pre>                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 500       | Server Error | <pre>message: {"message": "Metric (CurrentGrouargetState) not found on running StatServer", "exception": "com.genesyslab.gsg.services.st</pre>                                                                                                                                                                                                                                                                                                                                            |

### Examples with Multiple Statistics

#### Request

```
$ curl -v -u default:password -H "Content-Type: application/json" -X POST --data '{
"stat1": {
  "objectId": "fakeAG",
  "objectType": "GroupAgents",
  "tenant": "Environment",
  "tenantPassword": "",
  "metric": "TotalLoginTime",
  "filter": ""
},
  "stat2": {
    "objectId": "KSippola",
    "objectType": "Agent",
    "tenant": "Environment",
    "tenantPassword": "",
    "metric": "TotalLoginTime",
    "filter": ""
  }
}' http://localhost:8080/genesys/3/statistics
> Content-Type: application/json
>
< HTTP/1.1 200 OK
< Content-Type: application/json; charset=UTF-8
{
  "stat2": {
    "status": "ok",
    "value": 0
  },
  "stat1": {
    "status": "error",
    "value": "Agents Group 'fakeAG' (Tenant 'Environment') not found"
  }
}
```

### EWT APIs

---

In 8.5.2, the Estimated Waiting Time (EWT) APIs were refactored. These APIs, available to query EWT, use different calculation types to provide the Estimated Waiting Time. These APIs return either a JSON object presentation that describes the information in the virtual queue or a collection of such objects (one per every matched virtual queue the call is in). GMS retrieves all of the results from URS.

### Important

In your GMS configuration, add a connection to an active URS to enable this service.

To provide Estimated Waiting Time, three methods are available:

- **ewt1—urs** calculation:

```
http://<urshost>:<ursport>/urs/call/max/lvq?name=VQ_Name&aqt=urs&tenant=TenantName
```

URS checks how fast interactions go through the virtual queue and how many interactions are still pending. URS ignores the current agent availability and does not immediately adjust the EWT if, for example, all of the agents handling the queue suddenly logout.

- **ewt2—urs2** calculation:

```
http://<urshost>:<ursport>/urs/call/max/lvq?name=VQ_Name&aqt=urs2&tenant=TenantName
```

Similarly to the first method, URS checks how fast interactions go through the virtual queue and how many interactions are pending. Additionally, URS takes into account the agents who have historically been handling interactions of the Virtual Queue. If all of these agents logout, URS notices and adjusts the EWT value to a very high number like 10000 for example.

- **ewt3—stat** calculation:

```
http://<urshost>:<ursport>/urs/call/max/lvq?name=VQ_Name&aqt=stat&tenant=TenantName
```

Estimated Waiting Time is returned in seconds.

## GET - Query EWT from Stat Server

## GET /genesys/2/ewt/ewt1?vq={vq}

Retrieves the Estimated Waiting Time in seconds based on the **aqt=urs** calculation.

## URI Parameters

| Name      | Type                  | Description                                                                                                                                                                                                                                                                        |
|-----------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vq</b> | string<br><i>path</i> | Alias name of a virtual queue or comma-separated list of Virtual Queue alias names configured in a service . For example, vq=vq1 or vq=vq1,vq2,vq3<br><br>If you omit the vq parameter, the response provides EWT in seconds for all of the VQs which have a callback interaction. |

## GET /genesys/2/ewt/ewt2?vq={vq}

Retrieves the Estimated Waiting Time in seconds based on the **aqt=urs2** calculation.

## URI Parameters

| Name                | Type                  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vq</b> *required | string<br><i>path</i> | Alias name of a virtual queue or comma-separated list of Virtual Queue alias names configured in a service . For example, vq=vq1 or vq=vq1,vq2,vq3<br><br>If you omit the vq parameter, the response provides EWT for all of the configured VQs.<br><br>You can also query the EWT of a DN group by adding .GQ to the name of the VQ group. For example, if the name of the VQ group is VQG_HR_ALL_en, pass vq=VQG_HR_ALL_en.GQ in your query. |



## GET /genesys/2/ewt/ewt3?vq={vq}

Retrieves the Estimated Waiting Time in seconds based on the **agt=stat** calculation.

### URI Parameters

| Name                | Type                  | Description                                                                                                                                                                                                                                                 |
|---------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vq</b> *required | string<br><i>path</i> | Alias name of a virtual queue or comma-separated list of Virtual Queue alias names configured in a service . For example, vq=vq1 or vq=vq1,vq2,vq3<br><br>If you omit the vq parameter, the response provides EWT in seconds for all of the configured VQs. |

## POST – Query EWT from Stat Server

### POST/genesys/2/ewt/ewt1/

Retrieves the Estimated Waiting Time in seconds based on the **agt=urs** calculation.

### JSON Body

*Can be empty or null*

| Name                | Type         | Description                                                                                                                                                                                                                             |
|---------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vq</b> *required | String array | Alias name of a virtual queue or comma-separated list of Virtual Queue alias names configured in a service. For example:<br><br><pre>{<br/>  "vq": ["VQ_GMS_Callback1",<br/>        "VQ_GMS_Callback2", "VQ_GMS_Callback3"]<br/>}</pre> |

If you omit the `vq` parameter, the response provides EWT in seconds for all of the configured VQs.

## POST/genesys/2/ewt/ewt2

Retrieves the Estimated Waiting Time in seconds based on the `aqt=urs2` calculation.

### JSON Body

*Can be empty or null*

| Name                | Type         | Description                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vq</b> *required | String array | Alias name of a virtual queue or comma-separated list of Virtual Queue alias names configured in a service . For example:<br><br><pre>{<br/>  "vq": [ "VQ_GMS_Callback1",<br/>          "VQ_GMS_Callback2", "VQ_GMS_Callback3"]<br/>}</pre><br>If you omit the <code>vq</code> parameter, the response provides EWT in seconds for all of the configured VQs. |

## POST/genesys/2/ewt/ewt3

Retrieves the Estimated Waiting Time in seconds based on the `aqt=stat` calculation.

### JSON Body

*Can be empty or null*

| Name      | Type         | Description                                                                        |
|-----------|--------------|------------------------------------------------------------------------------------|
| <b>vq</b> | String array | Alias name of a virtual queue or comma-separated list of Virtual Queue alias names |

|  |  |                                                                                                                                                                                                                                               |
|--|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |  | <p>configured in a service. For example:</p> <pre>{   "vq": ["VQ_GMS_Callback1",     "VQ_GMS_Callback2", "VQ_GMS_Callback3"] }</pre> <p>If you omit the vq parameter, the response provides EWT in seconds for all of the configured VQs.</p> |
|--|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Responses

200 OK

| 200 OK                          |                                                                                                                                                        |                                                                                       |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Response Body<br>(JSON content) | JSON-formatted string of information per virtual queue.<br>The JSON objects describing information in the virtual queue have the following properties: |                                                                                       |
|                                 | Property                                                                                                                                               | Description                                                                           |
|                                 | time                                                                                                                                                   | UTC timestamp when the call entered in the virtual queue.                             |
|                                 | wt                                                                                                                                                     | Time in seconds that the call is in the virtual queue (effectively CurrentTime-time). |
|                                 | calls                                                                                                                                                  | Current number of all calls in the virtual queue.                                     |
|                                 | wcalls                                                                                                                                                 | Number of waiting calls in the virtual queue.                                         |
|                                 | pos                                                                                                                                                    | Position of the call in the virtual queue.                                            |

|  | Property | Description                                                                                               |
|--|----------|-----------------------------------------------------------------------------------------------------------|
|  | wpos     | Waiting position of the call in the virtual queue.                                                        |
|  | priority | Calls priority in the virtual queue. Absent if scaling is used.                                           |
|  | aqt      | Average quitting rate of calls from the virtual queue. May be skipped if unknown.                         |
|  | ewt      | Expected waiting time for the call in seconds.                                                            |
|  | hit      | Percentage of calls distributed into the virtual queue. Its value is -1 if no calls were distributed yet. |
|  | clc      | Short data information about the source of the reported aqt and/or ewt.                                   |

## 500 Internal Server Error

| Name                      | Value                                                                                                                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 500 Internal Server Error |                                                                                                                                                                                           |
| code                      | 50001                                                                                                                                                                                     |
| phrase                    | NO_EWT_CONTENT                                                                                                                                                                            |
| message                   | There have been no interactions in VQ VQ_GMS_Callback so the EWT is unknown. To make URS report EWT for virtual queue, URS need (at least one time) to run strategy where this VQ is used |
| exception                 | com.genesyslab.gsg.services.services.EwtException                                                                                                                                         |
| properties                | { "time": <UTC timestamp> }                                                                                                                                                               |

---

| Name                      | Value                                                          |
|---------------------------|----------------------------------------------------------------|
| 500 Internal Server Error |                                                                |
| code                      | 50002                                                          |
| phrase                    | NO_TENANT_FOUND                                                |
| message                   | The tenant name is null or empty, check configuration          |
| exception                 | com.genesyslab.gsg.services.services.ResourceNotFoundException |
| properties                | { "time": <UTC timestamp> }                                    |

## Examples

GET with one provided VQ name:

GET http: //localhost:8080/genesys/2/ewt/ewt1?vq=VQ\_GMS\_Callback  
Result

```
200 OK
{
  "hit": -1,
  "ewt": 37.5,
  "calls": 1,
  "pos": 2,
  "aqt": 10000,
  "wpos": 2,
  "time": 1515617935,
  "clc": "CCAA100",
  "wt": 0,
  "wcalls": 1
}
```

GET with no provided VQ name:

GET http: //localhost:8080/genesys/2/ewt/ewt2  
Result

200 OK

```
{
  "VQ_GMS_Callback1": {
    "time": 1515617939,
    "wt": 0,
    "calls": 1,
    "wcalls": 1,
    "pos": 2,
    "wpos": 2,
    "aqt": 10000,
    "ewt": 20.9,
    "hit": -1,
    "clc": "AFAA100"
  },
  "VQ_GMS_Callback2": {
    "time": 1515648959,
    "wt": 0,
    "calls": 1,
    "wcalls": 1,
    "pos": 2,
    "wpos": 2,
    "aqt": 10000,
    "ewt": 99.3,
    "hit": -1,
    "clc": "BvAA100"
  },
  "VQ_GMS_Callback3": {
    "time": 1515617939,
    "wt": 0,
    "calls": 1,
    "wcalls": 1,
    "pos": 2,
    "wpos": 2,
    "aqt": 10000,
    "ewt": 46.2,
    "hit": -1,
    "clc": "CCAA100"
  }
}
```

GET for a list of VQs; one of them does not exist:

GET http: //localhost:8080/genesys/2/ewt/ewt3?vq=VQ\_GMS\_Callback1,VQ\_GMS\_Callback3  
Result

200 OK

```
{
  "VQ_GMS_Callback1": {
    "time": 1515617939,
    "wt": 0,
    "calls": 1,
    "wcalls": 1,
    "pos": 2,
    "wpos": 2,
    "aqt": 10000,
    "ewt": 20.9,
    "hit": -1,
    "clc": "AFAA100"
  },
  "VQ_GMS_Callback3": {
    "time": 1515617939,
    "wt": 0,
    "calls": 1,
    "wcalls": 1,
    "pos": 2,
    "wpos": 2,
    "aqt": 10000,
    "ewt": 46.2,
    "hit": -1,
    "clc": "CCAA100"
  }
}
```

GET http: //localhost:8080/genesys/2/ewt/ewt3?vq=VQ\_GMS\_Callback1,VQ\_GMS\_Callback3  
Result

200 OK

```
{
  "VQ_GMS_Callback1": {
    "time": 1515617939,
    "wt": 0,
    "calls": 1,
    "wcalls": 1,
    "pos": 2,
    "wpos": 2,
```

```
    "aqt": 10000,  
    "ewt": 20.9,  
    "hit": -1,  
    "clc": "AFAA100"  
  },  
  "VQ_GMS_Callback3": null  
}
```

### POST with a list of VQs:

```
POST http: //localhost:8080/genesys/2/ewt/ewt1  
Body: {  
  "vq": [  
    "VQ_GMS_Callback", "VQ_GMS_Callback_Out"  
  ]  
}  
Result  
  
200 OK  
{  
  "VQ_GMS_Callback": {  
    "time": 1515617939,  
    "wt": 0,  
    "calls": 1,  
    "wcalls": 1,  
    "pos": 2,  
    "wpos": 2,  
    "aqt": 10000,  
    "ewt": 20.9,  
    "hit": -1,  
    "clc": "AFAA100"  
  },  
  "VQ_GMS_Callback_Out": {  
    "time": 1515617939,  
    "wt": 0,  
    "calls": 1,  
    "wcalls": 1,  
    "pos": 2,  
    "wpos": 2,  
    "aqt": 10000,  
    "ewt": 46.2,  
    "hit": -1,  
  }  
}
```



```
    "clc": "CCAA100"
  }
}
```

GET Operation failed (no EWT info returned from URS):

GET http: //localhost:8080/genesys/2/ewt/ewt1?vq=VQ\_GMS\_Callback  
Result

500 Internal Server Error

```
{
  "exception": "com.genesyslab.gsg.services.services.EwtException",
  "code": 50001,
  "phrase": "NO_EWT_CONTENT",
  "message": "There have been no interactions in VQ VQ_GMS_Callback so the EWT is unknown. To make URS report EWT for virtual queue,
  URS need (at least one time) to run strategy where this VQ is used.",
  "properties": {
    "time": "2018-01-10T22:12:56.315Z"
  }
}
```

GET Operation failed (no tenant name was found):

GET http: //localhost:8080/genesys/2/ewt/ewt1?vq=VQ\_GMS\_Callback  
Result

500 Internal Server Error

```
{
  "exception": "com.genesyslab.gsg.services.services.ResourceNotFoundException",
  "code": 50002,
  "phrase": "NO_TENANT_FOUND",
  "message": "The tenant name is null or empty, check configuration.",
  "properties": {
    "time": "2018-01-10T22:12:56.315Z"
  }
}
```

## Peek Multiple Statistics - V3 (StatisticController)

This request gets multiple statistic values from several statistics.

With previous version, when one statistic object type no longer exists in the system, the query of multiple statistics containing one of this removed object type will fail even if other object types exist. With V3, when subscribing to several statistics, the operation would not be stopped on the first statistics item that fails (for example statistic does not exist).

Table 25. Operation

|                                                                                                                                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Discontinued item placeholder request Method POST URL                                                                                                                                                                                       |
| /genesys/3/statistics                                                                                                                                                                                                                       |
| Parameter Type Mandatory Description Header Parameters                                                                                                                                                                                      |
| Cache-Control: max-age=XX                                                                                                                                                                                                                   |
| A number of seconds                                                                                                                                                                                                                         |
| no                                                                                                                                                                                                                                          |
| The max-age value used to check if GMS has to recalculate the statistic. If the peek statistic time window is greater than maxAge, GMS recalculates the statistic value. If the value is not present, it returns the latest value in cache. |
| URL Parameters                                                                                                                                                                                                                              |
| Body                                                                                                                                                                                                                                        |
| The body should be JSON consisting of different items representing the key/value pairs associated with the statistic (objectId, objectType, tenant, tenantPassword, metric, notificationMode, filter).                                      |
| <ul style="list-style-type: none"><li>NotificationMode can be NoNotification, Reset, or Immediate.</li><li>filter is the business attribute value to use to filter the results.</li></ul>                                                   |

Table 26. Operation response HTTP code 200 HTTP Message

OK

### HTTP Header

Content-Type: application/json;charset=UTF-8

### Body

A json object representing a structure with values

If a problem occurs during operation, the following status codes are returned:

Table 27. Operation errors HTTP code HTTP Message HTTP Body 200

### OK

message: { "stat2": { "status": "ok", "value": 0 }, "stat1": { "status": "error", "value": "Agents Group fakeAG (Tenant Environment) not found" } }. It means that, instead of getting a 400 Bad request response, you are able to retrieve statistics, even if one of them is incorrect.

### 401

#### Unauthorized

Access to API refused

### 403

#### Forbidden

message: {"message":"Wrong parameter","exception":null}

### 500

#### Server Error

message: { "stat1": { "status": "error", "value": "Metric (CurrentGrouargetState) not found on running StatServer" } }

Example of request:

Operation example

```
$ curl -v -u default:password -H "Content-Type: application/json" -X POST --data '{
"stat1": {
  "objectId": "fakeAG",
  "objectType": "GroupAgents",
  "tenant": "Environment",
  "tenantPassword": "",
  "metric": "TotalLoginTime",
  "filter": ""
},
  "stat2": {
    "objectId": "KSippola",
    "objectType": "Agent",
    "tenant": "Environment",
    "tenantPassword": "",
    "metric": "TotalLoginTime",
    "filter": ""
  }
}'
```

```
http://localhost:8080/genesys/3/statistics
> Content-Type: application/json
>
< HTTP/1.1 200 OK
< Content-Type: application/json; charset=UTF-8
{
  "stat2": {
    "status": "ok",
    "value": 0
  },
  "stat1": {
    "status": "error",
    "value": "Agents Group 'fakeAG' (Tenant 'Environment') not found"
  }
}
```

## Configuration

### Stat Server Connection

In order to use the Stat Server API, there must be a connection to Stat Server in the GMS Application. You can create the connection in Configuration Manager on the *Connections* tab. See [Creating and Configuring the GMS Application Cluster Object](#).

You can add several Stat Servers in the *Connection* tab; this feature is used in case of different statistic definitions in the Stat Servers. GMS will open the statistic on the Stat Server to which the statistic belongs to. In the case of the same statistic definition in Stat Servers, GMS will take the first Stat Server that contains the statistic definition.

### ADDP Setting

Open Stat Server in the GMS *Connection* tab and set the connection protocol to *addp*. Set the values for the Local Timeout and Remote Timeout, and then select the Trace mode. See [Implementing ADDP](#) for more information.

#### Important

The ADDP traces are only visible on the Stat Server side.

The following example shows an ADDPtrace in Stat Server logs:

```
-AP[10] -<-2168 @15:37:30.4540
```

```
-Ap[10] ->-2168 @15:37:30.4560
```

### High Availability

If Stat Servers (defined in GMS connections) are configured to use High Availability (HA) (Primary/Backup Stat Server), in the case of a lost connection with the primary Stat Server, the Stat Server API will switch to the backup Stat Server.

## Subscribe to Statistic Server Event Notifications

You can receive event notifications sent by the Statistics Server by using the CometD channel. To do so:

1. Register for GMS CometD channel.
2. Subscribe for a list of statistics through the new API: **POST /genesys/2/statistics**.

### Important

This Statistics API currently supports polling mode.

## Register for GMS CometD Channel

Create a client that will listen to CometD events sent by GMS, as shown in the following Node JS example:

```
var faye = require("faye");
var request = require('request');
// subscribe GMS comet
var referenceId;
var client = new faye.Client("http://localhost:8080/genesys/cometd");
client.setHeader("gms_user", "123456");
var subscr = client.subscribe("/_genesys", function (message) {
  var stats = message["message"]
  var statReferenceId = stats["statReferenceId"]
  ///...
  client.disconnect();
});
```

## Subscribe to Statistics through the Statistics API

Use the API to subscribe to a list of statistics and retrieve for each of them the reference ID of the Stat Server. Then, you will receive CometD event notifications associated with these reference IDs.

### Important

You must subscribe with the same gms\_user ID as the one used for the CometD client.

### Operation

| POST /genesys/2/statistics                                                                                                                                                                                                                                                                                                                       |               |           |                                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|----------------------------------------------------------------|
| Parameter                                                                                                                                                                                                                                                                                                                                        | Type          | Mandatory | Description                                                    |
| Header Parameters                                                                                                                                                                                                                                                                                                                                |               |           |                                                                |
| Content-type                                                                                                                                                                                                                                                                                                                                     |               | Yes       | application/json; charset=UTF-8                                |
| gms_user                                                                                                                                                                                                                                                                                                                                         | String (UUID) | Yes       | The user ID that has been used in CometD at registration time. |
| Body: The body is a JSON structure that lists the statistics to get notifications for.<br>For example:<br><pre>{   "stat1": {     "objectId": "kmilburn",     "objectType": "Agent",     "tenant": "Environment",     "tenantPassword": "",     "metric": "TotalLoginTime",     "filter": ""   },   "stat2": {     "objectId": "KSippola",</pre> |               |           |                                                                |

**POST /genesys/2/statistics**

```
{  "objectType": "Agent",
  "tenant": "Environment",
  "tenantPassword": "",
  "metric": "TotalLoginTime",
  "filter": "Bronze"
}
```

**Response**

The response contains the reference IDs from the Stat Server subscribed statistics.

| HTTP code    | 200                                                                                                                                                                                                                                  |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HTTP Message | OK                                                                                                                                                                                                                                   |
| Body         | <p>A JSON array of key/value pairs, where:</p> <ul style="list-style-type: none"><li>• The key is the name of the subscribed statistics.</li><li>• The value is the reference ID of the Stat Server subscribed statistics.</li></ul> |

For example:

```
200 OK
{"stat1":1958339548,"stat2":1329710246}
```

**Errors**

| HTTP Code    | 500                                                                                                           |
|--------------|---------------------------------------------------------------------------------------------------------------|
| HTTP Message | Server Error                                                                                                  |
| Body         | <ul style="list-style-type: none"><li>• {"message":"Could not read JSON: Unexpected character ('\"'</li></ul> |



| HTTP Code | 500                                                                                                                                                                                                                                                                       |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <pre>(code 34)): [...]}.</pre> <ul style="list-style-type: none"><li>• {"message":"Error for stat1: Supplied Object type does not belong to specified Stat Type.",<br/>"exception":"com.genesyslab.gsg.services.statistic.StatServer<br/>EventErrorException"}.</li></ul> |

## Example

The following node JS sample shows how to subscribe statistics with this API.

```
var request = require('request');
// send request to subscribe stat using gms_user of comet subscription
request({
  url: 'http://localhost:8080/genesys/2/statistics', //URL to hit
  headers: {
    'Content-Type': 'application/json',
    'gms_user': '123456'
  },
  method: 'POST',
  json: true, // output data is JSON
  json: { // input data is JSON too
    "stat2": {
      "objectId": "KSippola",
      "objectType": "Agent",
      "tenant": "Environment",
      "tenantPassword": "",
      "metric": "TotalLoginTime",
      "filter": ""
    }
  }
}, function (error, response, body) {
  if (error) {
    ///...
  } else {
    referenceId = body["stat2"];
    ///...
  }
});
```

```
});
```

As a result of the subscription, you would receive the following reference IDs:

```
200 OK
{"stat1":1958339548,"stat2":1329710246}
```

As a result, CometD Polling responses include these reference IDs too:

```
[
  {
    "data": {
      "id": "8f8dc3a0d00311e5845a0de0f4fa8277",
      "message": {
        "statValue": "0", "statReferenceId": "1958339548",
        "tag": "service.statistic.push.1958339548",
        "channel": "/_genesys"},
      "id": "55", "successful": true, "channel": "/meta/connect"}
    }
  ]
[
  {
    "data": {
      "id": "9560da60d00311e5845a0de0f4fa8277",
      "message": {
        "statValue": "0", "statReferenceId": "1329710246",
        "tag": "service.statistic.push.1329710246",
        "channel": "/_genesys"},
      "id": "56", "successful": true, "channel": "/meta/connect"}
    }
  ]
]
```

## Limitations

- CometD requests TTL is 120 seconds (by default).
- The statistics filter subscription is set to 10000 seconds, then the subscription is removed and you must send back the same stat request before the end of TTL subscription.
- You cannot define a statistic in Configuration Server for the GMS application that will be automatically subscribed at GMS startup. You must subscribe to the statistics as detailed above.