



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Mobile Services Deployment Guide

Configuring the ORS-based Services

5/2/2025

Configuring the ORS-based Services

Now that the basic scenarios are working, let's get started with the ORS-based advanced scenarios.

Contents

- **1 Configuring the ORS-based Services**
 - 1.1 Prerequisites
 - 1.2 Step 1: GMS Service - Samples
 - 1.3 Step 2: Inbound SCXML Service - Voice
 - 1.4 Step 3: Inbound SCXML Service - Chat
 - 1.5 Next Steps

Prerequisites

You must have completed the following:

1. [Configured the dependencies.](#)
2. [Configured the Builtin services.](#)
3. [Tested the Builtin services.](#)

Step 1: GMS Service – Samples

Why:

This service is responsible for receiving the GMS request from the sample application.

How:

GMS Service Management UI > Services > Configured Services

Procedure:

1. Click Add Service
2. Set Configure Service = callback
3. Set Service Name = samples.
4. Set Common Default Configuration = samples
5. Click Save.
6. Set `_target` = `<router>` Example: `Customer_Service@Stat_Server.GA`
7. Set `_urs_virtual_queue` = `GMS_VQ_SIP_Switch`
8. Set `_route_point` = `8999`
9. Set service property `_chat_endpoint` = `Environment:gms_ors` (or `Resources:gms_ors` if single tenant).

Step 2: Inbound SCXML Service - Voice

Why:

This inbound service matches the voice call with an existing GMS service. If a matching service is found, it moves the interaction to the GMS service (ORS session), which attaches the GMS User Data, and routes the call to the agent.

How:

- Configuration Manager > Switches > SIP_Switch
- Configuration Manager > Scripts

Procedure:

1. Create a route point associated with the access number configured in the procedure [Resource Group Add Access Number](#).
2. Set Annex > Orchestration section > application = script:GMSInbound.Voice.GMSMatchORS.
3. Create an enhanced routing script GMSInbound.Voice.GMSMatchORS.
4. Set Annex > Application section > url = http://<gmshost:gmsport>/genesys/1/document/service_template/callback/src-gen/IPD_Voice_GMSMatch.scxml
5. Set Annex > ApplicationParms/app_find_agent_timeout = 30
6. Set Annex > ApplicationParms/app_match_gms_builtin = false
7. Set Annex > ApplicationParms/app_no_match_target = <target> (Example: All_Standard_Agents@Stat_Server.GA)
8. Set Annex > ApplicationParms/app_require_access_code = false
9. Set Annex > ApplicationParms/app_require_ani = true
10. Set Annex > ApplicationParms/app_treatment_waiting_for_agent = <blank> (A blank value will force the service to use a packaged music file.)

Step 3: Inbound SCXML Service - Chat

Why:

This inbound service attaches the GMS user data to the interaction, and routes the interaction to the agent.

How:

- Configuration Manager > Chat Server
- Configuration Manager > Scripts

Procedure:

1. Go to Configuration Manager > Chat Server.
2. Create an end point that was specified in the procedure [GMS Service Create Service request chat](#) (sub-step 6):
 - gms_ors = GMSInbound.Chat.QueueORS
3. Go to Configuration Manager > Scripts.
4. Create interaction queue that you just specified, above.

- Name: `GMSInbound.Chat.QueueORS`
 - Set Annex > Orchestration/application = `script:GMSInbound.Chat.QueueORS.Routing`
5. Create an interaction queue view.
- Name: `GMSInbound.Chat.QueueORS.View 1`
 - Set Annex > View/Queue = `GMSInbound.Chat.QueueORS`
6. Create an Enhanced Routing Object that you just specified, above.
- Name: `GMSInbound.Chat.QueueORS.Routing`
 - Set Annex > Application/url = `http://<gms_host>:<gms_port>/genesys/1/document/service_template/callback/src-gen/IPD_Chat_QueueORS.scxml`
 - Set Annex > ApplicationParms/app_find_agent_timeout = `30`
 - Set Annex > ApplicationParms/app_match_gms_builtin = `false`
 - Set Annex > ApplicationParms/app_no_match_target = `<target>` (Example: `All_Standard_Agents@Stat_Server.GA`)

Next Steps

[Test the ORS-based Services](#)