



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Rules System Deployment Guide

The [log4j.properties](#) File

## The log4j.properties File

The `log4j.properties` file is used to configure initial logging for the Rules Engine and for the Genesys Rules Authoring Tool. Once the Rules Engine and GRAT are initialized, logging is done through the configured Application options. The `log4j.properties` file contains logging attributes that are used during the startup of the application, before the configured log settings are read by Configuration Server. In general, you should not have to modify this file and you can accept the default values. But should you need to change the defaults, perform the steps in the following procedure:

### Procedure

1. Locate the `log4j.properties` file. This file can be found in the `.war` file, which is located in the installation directory.
2. Extract the `.war` file by using WinZip or a similar tool for extraction. (For the Rules Engine and the Rules Authoring Tool, the `.war` files are named `genesys-rules-engine.war` and `genesys-rules-authoring.war`, respectively).
3. Open the file in a text editor, and update any logging parameters.
4. Save the file.
5. Add the modified `log4j.properties` file back into the original `.war` file by using WinZip (or a similar tool). Be very careful to preserve the "path" of that file during this step.

### Locating Log Files

Before connecting to Configuration Server, GRAT and GRE will log by default to the relative path:

- `"logs/GRATInit"`
- `"logs/GREInit"`

These logs are useful in debugging start-up issues; for example, if GRAT or GRE are unable to connect to Configuration Server.

- **In UNIX based systems**, these initial logs can be found under your application servers "logs" directory.
- **In Windows based servers**, these initial logs can be found in the `\Windows\SysWOW64\logs` directory.

You can change the initial location of these logs by editing the `log4j.properties` file as described in this section.

After GRAT or GRE connect to Config Server, the log location is determined by the application's configuration options (log section).