

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Rules System Deployment Guide

Deploying GRE in Genesys Administrator

Contents

- 1 Deploying GRE in Genesys Administrator
 - 1.1 Prerequisites
 - 1.2 Procedure Summary
 - 1.3 Procedure
 - 1.4 Next Steps

Deploying GRE in Genesys Administrator

Prerequisites

To install GRE on Configuration Servers 8.1.0 or later, Genesys Administrator 8.1.0 or later is required.

Procedure Summary

- 1. Import the installation package into Genesys Administrator.
- 2. Install the GRE IP.
- 3. Configure the Rules Engine application.

Procedure

Import the installation package into Genesys Administrator.

- 1. On the **Deployment** tab of Genesys Administrator, select **Import**.
- 2. Select Installation CD-ROM.
- 3. Click Next.
- 4. Browse to the **MediaInfo.xml** file on the CD or the CD image location on the network (the path must be in UNC format).
- 5. Click Next.
- 6. To import the installation package, select GRE for your operating system as well as the appropriate type in the list:
 - For Management Framework 8.1, the type is Business Rules Execution Server.
 - For Management Framework 8.0 and earlier, the type is Genesys Generic Server.
- 7. Select **Next** to start the import.
- 8. Click **Finish** when the import is complete.

Install the GRE IP

 Select the **Deployment** tab in Genesys Administrator. The list of installation packages will now display GRE.

- 2. Right-click and select **Install Package** for the IP for your operating system and type.
- 3. Click **Next** to start the installation wizard. The following parameters must be defined/selected:
 - a. **Application Name** for the GRE application
 - b. Target Host—The host to which the .war file will be copied during the installation procedure.
 - c. Working Directory—The directory in which the .war file will be created.
 - d. Client Side IP Address (optional).
 - e. Client Side Port (optional).
 - f. Configuration Server hostname.
 - g. Configuration Server port.

Important

For a secure connection, the Configuration Server port should be of type Auto Detect (Upgrade).

- h. Connection delay time in seconds
- i. Reconnect Attempts.

Configure the Rules Engine application

- 1. In the **[Server Info]** section, verify the default listening port, as well as the connector port on which the Rules Engine Servlet receives requests:
 - The **ID** value is the name of the Rules Engine web application. The default name of this application is genesys-rules-engine.
 - The **Listening port** is the connector port of the servlet container. For example, on Tomcat the default listening port is 8080.
 - The Connection Protocol must be http.
- 2. On the **Tenants** tab, add the Tenants that will be available to the Rules Engine.
- 3. On the **Connections** tab, add a connection to Message Server if you want to use network logging.
- 4. On the **Options** tab, configure options. In addition to the standard logging options that you can configure, you can configure an option named **fileEncoding** in the **[log]** section. **fileEncoding** specifies the encoding that is to be used during creation of the log file, for example, UTF-8. This value is optional. If you do not specify this option, the server's locale information will determine the log file encoding. This option is available for both GRE and GRAT. Also, the **log4j2.xml** file that is included in both components supports a similar option, **log4j.appender.runtime.Encoding**. The **log4j2.xml** file is used for initial log configuration prior to the reading of the log configuration from the Configuration Server database.
- 5. There are several optional configuration options to work with in the Configuration Options Reference Guide.
- 6. Save your changes.

Deploy the **genesys-rules-engine.war** file to your application server. See Deploying the .WAR files.