



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Skills Management Installation Guide for Microsoft Azure

Optional Command Line Parameters

Optional Command Line Parameters

The following parameters can be passed into the setup script using the following format -'parameter name' 'value' (without apostrophes, Boolean values are \$true and \$false):

Parameter	Description	Data type	Required
Name	The name of the web site	String	✓
ResourceGroupName	The name of the resource group	String	
SqlDatabaseUserName	Username for the SQL database	String:Defaults to "slsuser"	
SqlDatabasePassword	Username for the SQL database	SecureString	
StartIPAddress	The starting address of the range of IP addresses in the SQL Azure firewall rule to allow access from the local machine.	String	✓
EndIPAddress	The last address of the range of IP addresses in the SQL Azure firewall rule	String	
PortalName	The virtual directory to use for Portal	String	
UseHttps	Whether to use HTTPS or not	Boolean	
DbPricingTier	The database pricing tier to use	String (Basic, Free, Shared, Standard, Premium)	
WebAppPricingTier	The web app pricing tier to use	String	
MsgSendEveryNMinutes	Delay in minutes between the sending of email notifications	Integer	
MsgFromAddress	From address used for sent email notifications	String	
MsgNumberOfSendAttempts	Number of email sending attempts	Integer	
MsgSubject	Subject for feedback assessment emails	String	
MsgMessageBody	Body for feedback assessment emails	String	
MsgUseDefaultCredentials	Whether to use default	Boolean	

Parameter	Description	Data type	Required
	credentials for SMTP server		
MsgUsername	username for SMTP server	String	
MsgPassword	password for SMTP server	SecureString	
MsgPort	port for SMTP server	Integer	
MsgUseSSL	Whether to use SSL for SMTP server	Boolean	
MsgSMTPServer	SMTP Server	String	
MsgEnableOutlookMessages	Enable outlook messages	Boolean	
MsgOutlookDefaultFrom	use default from address for email notifications	String	
MsgUseDefaultOrganizer	Use default Organizer	Boolean	
Branding	Use non-default branding (Default/ Genesys/Teleopti)	String	
EnableAlwaysOn	Enable Always On for the web site. This will prevent the web site shutting down when there is no traffic. It also allows the web jobs to continue running as scheduled.	Boolean	

Important

For passing SecureStrings to the command line parameters you will need to do the following:

```
Read-Host "Enter Password" -AsSecureString | ConvertFrom-SecureString | Out-File "C:\Temp\Password1.txt"
```

If you are passing 2 passwords, you will need to do the above twice into different files, then do the following:

```
$pass1 = Get-Content "C:\Temp\Password1.txt" | ConvertTo-SecureString
```

Then pass these variables to the script via the command line.

You must specify a password that meets the security and complexity requirements in place on your environment. (This may help - <https://msdn.microsoft.com/en-us/library/ms161959.aspx>)