



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

SIP Voicemail Administration Guide

Backing Up and Restoring GSVM Data

5/11/2025

Backing Up and Restoring GSVM Data

This section describes how to backup and restore data:

 [Backing Up Data Manually](#)

 [Restoring Backed Up Data Manually](#)

Backing Up Data Manually



Purpose: To back up a snapshot of all data that Genesys SIP Voicemail keeps in the server storage directory.

Start

1. Open the directory `GSVM/tools/bin`
2. Run the program `./datasnapshot` This command backs up Genesys SIP Voicemail data by saving snapshots to the directories `GSVM/storage/data/sipvm/snapshots` and `GSVM/storage/data/system/snapshots`.
3. Move or copy these directories (`GSVM/storage/data/sipvm/snapshots` and `GSVM/storage/data/system/snapshots`) to a backup location.

End

Notes:

- You do not need to stop GSVM to perform this backup procedure.
 - You can create a cron job to perform this backup automatically.
 - This manual backup procedure stores multiple backups; nothing is overwritten. You must manually delete older backups if limited disk space is an issue.
-

Restoring Backed Up Data Manually



Purpose: To restore a snapshot of all data that Genesys SIP Voicemail that you created using the procedure [Backing Up Data Manually](#). **Start**

1. Stop GSVM.
 2. Delete the contents of content of `GSVM/storage`.
 3. Copy from the directories in your backup location to `GSVM/storage/data/sipvm/snapshots` and `GSVM/storage/data/system/snapshots`.
 4. Start GSVM.
-

End

See [Starting and Stopping](#).