



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

SIP Voicemail HA Deployment Guide

Testing the Virtual IP control scripts (Windows)

5/1/2025

Testing the Virtual IP control scripts (Windows)

Start

1. Run the SC_VIP_DOWN.BAT script on the backup VM Server.
2. Run the SC_VIP_UP.BAT script on the primary VM Server.
3. Verify that the Virtual IP interface is running on the primary host by using the ipconfig command. For example:

```
@C:\GCTI\SWITCHOVER\1NIC>ipconfig
@Windows IP Configuration
@Ethernet adapter Local Area Connection:
@Connection-specific DNS Suffix . :
@IP Address. . . . . : 10.10.11.103
@Subnet Mask . . . . . : 255.255.255.0
@IP Address. . . . . : 10.10.11.101
@Subnet Mask . . . . . : 255.255.255.0
@Default Gateway . . . . . : 10.10.11.104
```

2. Verify that the Virtual IP interface is not running on the backup VM Server. For example:

```
@C:\GCTI\SWITCHOVER\1NIC>ipconfig
@Windows IP Configuration
@Ethernet adapter Local Area Connection:
@ Connection-specific DNS Suffix . :
@ IP Address. . . . . : 10.10.11.102
@ Subnet Mask . . . . . : 255.255.255.0
@ Default Gateway . . . . . : 10.10.11.104
```

3. Run the SC_VIP_DOWN.BAT script on the primary VM Server.
4. Run the SC_VIP_UP.BAT script on the backup VM Server.
5. Verify that the Virtual IP interface is running on the backup VM Server by using the ipconfig command. Output should appear similar to the following:

```
@Ethernet adapter Local Area Connection:
@Connection-specific DNS Suffix . :
@IP Address. . . . . : 10.10.11.103
@Subnet Mask . . . . . : 255.255.255.0
@IP Address. . . . . : 10.10.11.102
@Subnet Mask . . . . . : 255.255.255.0
@Default Gateway . . . . . : 10.10.11.104
```

End

Next Steps

[Application control scripts Windows](#)

OR

[Back To Task Table](#)