



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

GVP Documentation Supplement

GVP 8.1+ Handles Play Treatment and Play Application Differently

12/24/2025

GVP 8.1+ Handles Play Treatment and Play Application Differently

[Return to Corrections Table of Contents](#)

SUMMARY: The GVP 8.x Next Generation Interpreter (NGi) handles treatments differently. (GVP-15176)

The next publication of the [GVP 8.1 Application Migration Guide](#) will include this revision:

CHAPTER: Chapter 3: Migrating to GVP 8.1 NGi

SECTION: VoiceXML \$-Variables

ADD THIS NOTE to *Table 11: Mapping \$-Variable Functionality*, below \$sid\$ and above \$scriptdata\$:

Variable	Description	NGI Equivalent
\$sid\$	The value of the Script ID as generated by the Queue Adapter or the IVR Server Client.	Not supported
<p>Note: Script ID is a parameter supplied by the routing strategy during play treatment and play application.</p> <ul style="list-style-type: none">• GVP 7.x uses the GVP Interpreter (GVPI), which executes treatments in the 7.x studio application branches, based upon script ID.• GVP 8.1 and later use the Next Generation Interpreter (NGi), and the routing strategy supplies the treatment/application URL directly. The URL is sent by IVR Server to CTIC and then to MCP, where it is executed. (MCP still receives the Script ID, but does not use it.)		
\$scriptdata\$	The URL link to the page that the CFA generated in response to run script requests from the IVR Server Client.	Not supported.