



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

GVP 7.6 Documentation Supplement

Backup for Sending the ScriptID

12/21/2025

Backup for Sending the ScriptID

SUMMARY: The configuration instructions for FetchScriptIDfromURS require additional information.

DOCUMENT: The [Genesys Voice Platform 7.6 Reference Manual](#).

CHAPTER: Chapter 1: Element Management Provisioning System

SECTION: Provisioning a Customer, Step 2—GenesysCTI

ADD THIS NOTE under Step 6 on page 43:

Important

Because some switches may not be able to provide the proper DNIS, the FetchScriptIDfromURS option is set in Behind-the-Switch mode, and Genesys Framework is configured to provide the ScriptID when this happens. The details are:

1. Genesys Queue Adapter (GQA) receives the DNIS and ANI as a part of the CallInfoResp from IServer to CFA.
2. GQA receives the RESULT, CONNID and DNIS (set to the ScriptId value) as a part of the CallInfoResp from IServer to CFA.
3. GQA sends RESULT, CONNID and DNIS (set to the ScriptId value).
4. If the scriptID is not received, then GQA sends the ANI and DNIS that it received as part of CallInfoResponse from the IServer, along with the result and CONNID.