



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

GVP User Guide

Agent Interaction Layer

Contents

- 1 Agent Interaction Layer
 - 1.1 AIL Performance Test Statistics

Agent Interaction Layer

This chapter covers the actual performance test results done on Agent Interaction Layer (AIL) 7.5. It presents the following topic:

AIL Performance Test Statistics

Genesys conducted tests to measure the performance of AIL when connected to the Genesys Framework. These tests used voice-only, e-mail-only, and blended scenarios. All tests used AIL 7.5 (which is built with Platform SDK libraries).

Test Environment

Table 1 details the test environment used to arrive at the recommended limits for deploying the AIL-based applications.

Important

One basis for understanding the optimized results of all the tests in this section is the use of a dedicated 1 Gigabit network in the lab environment.

Table 1: AIL Test Environment Components

 Table 1: AIL Test Environment Components 			
Component	Host	Hardware	Operating System
Configuration Server 7.5 T-Server G3 7.5 Switch Simulator 6.5.300.02	Host_01	2x Xeon 3.4 GHz/cache 512 KB; 2 GB memory; dedicated 1-Gigabit Ethernet	Microsoft Windows 2003 Server
Component	Host	Hardware	Operating System
AIL 7.5	Host_04	2x Opteron Dual Core; 2.2 GHz/cache 512 KB; 4 GB memory; dedicated 1-Gigabit Ethernet	Microsoft Windows 2003 Server; (J2SDK), Standard Ed., 1.4.2_08
Universal Contact Server	Host_02	2x Xeon 3.4 GHz/cache 512	Microsoft Windows 2003

(UCS) 7.5 Interaction Server 7.5		KB; 2 GB memory; dedicated 1-Gigabit Ethernet	Server
Microsoft SQL Server 2000 (UCS Database)	Host_03	Intel Xeon 3.0 GHz /cache 512 KB; 2 GB memory; dedicated 1-Gigabit Ethernet	Microsoft Windows 2003 Server

Test Tools

The tests used the following steps according to contact center role.

Behavior of Voice Agents

Upon receiving a call, an agent:

1. Answers the call.
2. Waits for 10 seconds.
3. Sets the agent's status to NotReady.
4. Releases the call.
5. Waits for 2 seconds.
6. Becomes Ready.
7. Repeats these steps.

Behavior of E-Mail Agents

Upon receiving an e-mail, an agent:

1. Answers the incoming e-mail.
2. Replies with an outgoing e-mail.
3. Waits for 10 seconds.
4. Sets the agent's status to NotReady.
5. Sends the outgoing e-mail.
6. Waits for 2 seconds.
7. Becomes Ready.
8. Repeats these steps.