



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Widgets Reference

Configuration

Contents

- 1 Configuration
 - 1.1 Description
 - 1.2 Example
 - 1.3 Options

Configuration

Description

SendMessage and SendMessageService share the configuration namespace '_genesys.widgets.sendmessage'. SendMessage has UI options while SendMessageService has connection options.

Example

```
window._genesys.widgets.sendmessage = {  
  apikey: 'n3eNkgXXXXXXXXXXXXX',  
  dataURL: 'http://host:port/genesys/2/email',  
  userData: {},  
  
  SendMessageButton: {  
    enabled: true,  
    template: '<div>Email</div>',  
    effect: 'fade',  
    openDelay: 1000,  
    effectDuration: 300,  
    hideDuringInvite: true  
  }  
};
```

Options

Name	Type	Description	Default	Required
apikey	string	Apigee Proxy secure token	n/a	Yes, if using Apigee Proxy
dataURL	URL String	URL of GMS server	n/a	Always
ajaxTimeout	number	Number of milliseconds to wait before AJAX timeout	3000	n/a
userData	object	Arbitrary attached data to include with message	{}	n/a
uploadsEnabled	boolean	Enables file uploads to the server and enables the file upload	true	n/a

Configuration

Name	Type	Description	Default	Required
		feature in the SendMessage UI plugin.		