



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Widgets Reference

Configuration

Contents

- 1 Configuration
 - 1.1 Description
 - 1.2 Example
 - 1.3 Options

Configuration

Description

Calendar share the configuration namespace '_genesys.widgets.calendar'. Calendar has UI options.

Example

```

window._genesys.widgets.calendar = {
  showAvailability: true,
  numberOfDays: 5,
  hideUnavailableTimeSlots: false

  calendarHours: {
    interval: 10,
    allDay: {
      openTime: '09:00',
      closeTime: '23:59'
    }
  }
};

```

Options

Name	Type	Description	Default	Required
showAvailability	boolean	Enable/disable calendar to update the timeslots based on the callback availability. The unavailable timeslots are greyed out.	true	n/a
numberOfDays	number	The number of days to display on calendar starting today.	5	n/a
timeFormat	number/string	This sets the time format for the timestamps in this widget. It can be	12	n/a

Configuration

Name	Type	Description	Default	Required
		12 or 24.		
hideUnavailableTimeSlots	boolean	Show/hide the unavailable callback time slots.	false	n/a
calendarHours.interval	number	The time interval between each consecutive timeslot displayed on calendar.	15	n/a
calendarHours.allDay.openTime	time	Opening time in 'HH:MM' 24 Hr format.	17:00	n/a
calendarHours.allDay.closeTime	time	Closing time in 'HH:MM' 24 Hr format.	23:59	n/a