



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Widgets Reference

Configuration

Contents

- 1 Configuration
 - 1.1 Description
 - 1.2 Example
 - 1.3 Options

Configuration

Description

CallUs uses the configuration property `'_genesys.widgets.callus'`. You must specify all numbers and labels that appear in the CallUs UI.

Example

```

window._genesys.widgets.callus = callus: {
  contacts: [
    {
      displayName: 'Payments',
      i18n: 'Number001',
      number: '1 202 555 0162'
    },
    {
      displayName: 'Local',
      i18n: 'Number002',
      number: '202 555 0134'
    },
    {
      displayName: 'International',
      i18n: 'Number003',
      number: '0647 555 0131'
    }
  ],
  hours: [
    '8am - 8pm Mon - Fri',
    '10am - 6pm Sat - Sun'
  ]
};

```

Options

Name	Type	Description	Default	Required
contacts	array	An array of objects that represent phone numbers and their labels. The first number in this list will display as the larger, main	[]	true

Name	Type	Description	Default	Required
		<p>number. Phone labels can be set directly using the 'displayName' property or you can use String Names from your localization file by setting the String Name in the 'i18n' property. 'i18n' overrides 'displayName'.</p> <p>Ex:</p> <pre>{ "displayName": "Payments", "i18n": "Number001", "number": "1 202 555 0162" }</pre>		
hours	array	<p>Array of strings to show stacked in the business hours section. Strings here are freeform. See screenshots for ideas.</p>	[]	