



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Query identity

Query identity



GET /identities/\${identityId}

Contents

- [1 Query identity](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)
 - [1.4 Examples](#)

Description

Retrieves a given identity.

Operation

Method	GET		
URL	/identities/\${identityId}		
Name	Value	Mandatory	Description
URI Parameters			
\${identityId}	string	yes	Identity identifier.
include_visits	<ul style="list-style-type: none">truefalse	no	If true, the returned identity contains the reference list of associated visits.
include_visits_detail	<ul style="list-style-type: none">true (if include_visits=true)false	no	If true, the returned identity contains the associated visit resources. You can only use this parameter if include_visits is set to true.
include_sessions	<ul style="list-style-type: none">truefalse	no	If true, the returned identity contains the reference list of authentication sessions.
include_sessions_detail	<ul style="list-style-type: none">true (if include_sessions=true)false	no	If true, the returned identity contains the associated sessions. You can only use this parameter if include_sessions is set to true.
include_pages	<ul style="list-style-type: none">truefalse	no	If true, the returned identity contains the reference list of the associated pages.
include_pages_detail	<ul style="list-style-type: none">true (if include_pages=true)false	no	If true, the returned identity contains the associated pages. You can only use this parameter if include_pages is set to true.

Query identity

Method	GET		
include_events	<ul style="list-style-type: none">• true• false	no	If true, the returned identity contains the reference list of associated events.
include_events_detail	<ul style="list-style-type: none">• true (if include_events=true)• false	no	If true, the returned identity contains the associated events. You can only use this parameter if include_events is set to true.

<references />

Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

HTTP code	200
HTTP Title	OK
Body	JSON Identity .

Examples

The following operation retrieves the identity resource with pat.thompson@genesyslab.com ID.
Request

<http://192.168.73.246:9081/backend/data/identities/pat.thompson@genesyslab.com>

Response

```
HTTP/1.1 200 OK
Date: Wed, 12 Dec 2012 15:17:09 GMT
Content-Type: application/json; charset=UTF-8
Date: Wed, 12 Dec 2012 15:17:09 GMT
Accept-Ranges: bytes
Server: Restlet-Framework/2.1.0
Content-Length: 477
[{"eventIds":null,"events":null,"pageIds":null,"pages":null,
"sessionIds":null,"sessions":null,"identityId":"pat.thompson@genesyslab.com",
"name":null,"location":null,"entityInCS":null,"visitScope":"Authenticated",
"visitIds":null,"visits":null}]
```

