



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Query session

Query session



GET /sessions/\${sessionId}

Contents

- [1 Query session](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)

Description

Retrieves a specific session resource.

Operation

Method	GET		
URL	/sessions/\${sessionId}		
Name	Value	Mandatory	Description
URI Parameters			
\${sessionId}	string	yes	Authenticated session's identifier.
include_pages	<ul style="list-style-type: none">truefalse	no	If true, the returned session contains the reference list of the associated pages.
include_pages_detail	<ul style="list-style-type: none">true(if include_pages=true)false	no	If true, the returned session contains the associated pages. You can only use this parameter if include_pages is set to true.
include_events	<ul style="list-style-type: none">truefalse	no	If true, the returned session contains the reference list of associated events.
include_events_detail	<ul style="list-style-type: none">true(if include_events=true)false	no	If true, the returned session contains the associated events. You can only use this parameter if include_events is set to true.

<references />

Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

Query session

HTTP code	200
HTTP Title	OK
Body	Session