



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Query sessions by visit

Query sessions by visit



GET /visits/\${visitId}/sessions

Contents

- [1 Query sessions by visit](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)

Description

Retrieves the sessions for a given visit.

Operation

Method	GET		
URL	/visits/{visitId}/sessions		
Name	Value	Mandatory	Description
URI Parameters			
{visitId}	string	yes	visit identifier.
identityId	string	no	ID of the identity associated with the returned sessions.
age	integer	no	Sessions' maximum age in seconds. Older sessions will not be returned.
include_pages	<ul style="list-style-type: none">truefalse	no	If true, the returned sessions contain the reference list of the associated pages.
include_pages_detail	<ul style="list-style-type: none">true (if include_pages=true)false	no	If true, the returned sessions contain the associated pages. You can only use this parameter if include_pages is set to true.
include_events	<ul style="list-style-type: none">truefalse	no	If true, the returned sessions contain the reference list of associated events.
include_events_detail	<ul style="list-style-type: none">true (if include_events=true)false	no	If true, the returned sessions contain the associated events. You can only use this parameter if include_events is set to true.

<references />

Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

HTTP code	200
HTTP Title	OK
Body	JSON Array of Session resources .