

# **GENESYS**<sup>®</sup>

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# **API** Reference

Query visit

# Query visit

a**b**c

GET /visits/\${visitId}

#### Contents

- 1 Query visit
  - 1.1 Description
  - 1.2 Operation
  - 1.3 Response

### Description

Retrieves a given visit.

## Operation

| Method                  | GET   |           |  |
|-------------------------|---|-----------|--|
| URL                     | /visits/ <b>\${visitId}</b>   |           |  |
| Name                    | Value   | Mandatory | Description  |
| URI Parameters          |   |           |  |
| \${visitId}             | string  | yes       | Visit identifier.  |
| include_sessions        | • true<br>• false   | no        | If true, the returned<br>visit contains the<br>reference list of<br>authentication sessions.   |
| include_sessions_detail | <ul> <li>true<br/>(if include_sessions=<br/>true)</li> <li>false</li> </ul> | no        | If true, the returned<br>visit contains the<br>associated authentication<br>sessions. You can only<br>use this parameter if<br>include_sessions is<br>set to true. |
| include_pages           | • true<br>• false   | no        | If true, the returned<br>visit contains the<br>reference list of the<br>associated pages.  |
| include_pages_detail    | <ul> <li>true<br/>(if include_pages=<br/>true)</li> <li>false</li> </ul>    | no        | If true, the returned<br>visit contains the<br>associated pages. You<br>can only use this<br>parameter if<br>include_pages is set<br>to true.                      |
| include_events          | <ul><li>true</li><li>false</li></ul>  | no        | If true, the returned<br>visit contains<br>the reference list of<br>associated events.   |
| include_events_detail   | <ul> <li>true<br/>(if include_events=<br/>true)</li> <li>false</li> </ul>   | no        | If true, the returned<br>visit contains the<br>associated events.<br>You can only use this<br>parameter if<br>include_events is set<br>to true.                    |

<references />

#### Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this operation can return.

| HTTP code  | 200    |
|------------|--------|
| HTTP Title | ОК     |
| Body       | Visit. |