

# **GENESYS**<sup>®</sup>

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

### **API** Reference

Query session

## Query session

#### Contents

- 1 Query session
  - 1.1 Description
  - 1.2 Request
  - 1.3 Response

#### Description

This method retrieves a specific session resource.

#### Request

Method	GET		
URL	/sessions/ <b>\${sessionId}</b>		
Parameters			
Name	Value	Mandatory	Description
\${sessionId}	string	yes	Authenticated session's identifier.
include_pages	• true • false	no	If true, the returned session contains the reference list of the associated pages.
include_pages_detail	<ul><li>true(if include_pag es=true)</li><li>false</li></ul>	no	If true, the returned session contains the associated pages.You can only use this parameter if include_pages is set to true.
include_events	• true • false	no	If true, the returned session contains the reference list of associated events.
include_events_detail	<ul> <li>true (if include_events= true)</li> <li>false</li> </ul>	no	If true, the returned session contains the associated events. You can only use this parameter if include_events is set to true.

<references />

#### Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this request can return.

HTTP code	200
HTTP Title	ОК
Body	Session