



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Deployment Guide

Backend Server service:wmdb Section

# Backend Server service:wmdb Section

The configuration options in the `service:wmdb` section are used to control the settings for the Cassandra database embedded in the Backend Server.

## Contents

- [1 Backend Server service:wmdb Section](#)
  - [1.1 wmdb.limitIndexing](#)
  - [1.2 wmdb.retention.entity.all](#)

## wmdb.limitIndexing

Default Value: true

Valid Values: true, false

Changes Take Effect: After start/restart

This option limits the types of indexing produced by Web Engagement, thereby boosting the performance of the Backend Server and decreasing the amount of data generated by indexing operations. **Note:** when this option is enabled, some of the methods in the History REST API will not work. When this option is disabled, Web Engagement will generate all indexing data.

## wmdb.retention.entity.all

Default Value: 1

Valid Values: Any integer

Changes Take Effect: After start/restart

Specifies the time to live (TTL) for all entities in the Cassandra database, in the time units set in the [wmdb.retention.time-unit](#) option. The entities affected by this option are: event, page, session, visit, engagementattempt, useragent, and identity. This option is mandatory.

## wmdb.retention.entity.<object>

Default Value: The value of the [wmdb.retention.entity.all](#) option.

Valid Values: Any integer

Changes Take Effect: After start/restart

Specifies the time to live (TTL) for the selected entity, in the time units set in the [wmdb.retention.time-unit](#) option. Possible values for <object> are: event, page, session, visit, engagementattempt, useragent, and identity. This option is not mandatory.

## wmdb.retention.time-unit

Default Value: day

Valid Values: sec, min, hour, day, month

Changes Take Effect: After start/restart

Defines the time units for the expiration period set in the [wmdb.retention.entity.all](#) and [wmdb.retention.entity.<object>](#) options. This option is mandatory.