



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

[Query identities by visit](#)

Query identities by visit

Contents

- [1 Query identities by visit](#)
 - [1.1 Description](#)
 - [1.2 Request](#)
 - [1.3 Response](#)

Description

This method retrieves a list of identities for the given visit ID.

Request

Method	GET		
URL	/visits/\${visitId}/identities		
Parameters			
Name	Value	Mandatory	Description
include_visits	<ul style="list-style-type: none">• true• false	no	If true, each returned identity contains the reference list of associated visits.
include_visits_detail	<ul style="list-style-type: none">• true (if include_visits=true)• false	no	If true, each returned identity contains the associated visits resources. You can only use this parameter if include_visits is set to true.
include_sessions	<ul style="list-style-type: none">• true• false	no	If true, each returned identity contains the reference list of sessions.
include_sessions_detail	<ul style="list-style-type: none">• true (if include_session s=true)• false	no	If true, each returned identity contains the associated sessions.You can only use this parameter if include_sessions is set to true.
include_pages	<ul style="list-style-type: none">• true• false	no	If true, each returned identity contains the reference list of the associated pages.
include_pages_detail	<ul style="list-style-type: none">• true (if include_pages=true)• false	no	If true, each returned identity contains the associated pages. You can only use this parameter if include_pages is set to true.

Method	GET		
include_events	<ul style="list-style-type: none">• true• false	no	If true, each returned identity contains the reference list of associated events.
include_events_detail	<ul style="list-style-type: none">• true (if include_events=true)• false	no	If true, each returned identity contains the associated events. You can only use this parameter if include_events is set to true.
association	<ul style="list-style-type: none">• "Authenticated"• "Recognized"	no	Defines the type of association between the current visit and the returned identity.

Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this request can return.

HTTP code	200
HTTP Title	OK
Body	JSON array of Identity