



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Query visits by identity

Query visits by identity

Contents

- [1 Query visits by identity](#)
 - [1.1 Description](#)
 - [1.2 Request](#)
 - [1.3 Response](#)

Description

This method retrieves the visits for a given identity.

Request

Method	GET		
URL	/identities/\${identityId}/visits		
Parameters			
Name	Value	Mandatory	Description
\${identityId}	string	yes	Identity identifier.
age	integer	no	Visits' maximum age in seconds. Older visits will not be returned.
globalVisitID	string	no	Filters the visit results based on the given global Visit ID.
userAgent	string	no	Returns the visits matching the UserAgent field.
include_sessions	<ul style="list-style-type: none">truefalse	no	If true, the returned visits contain the reference list of sessions.
include_sessions_detail	<ul style="list-style-type: none">true (if include_session s=true)false	no	If true, the returned visits contain the associated sessions. You can only use this parameter if include_sessions is set to true.
include_pages	<ul style="list-style-type: none">truefalse	no	If true, the returned visits contain the reference list of the associated pages.
include_pages_detail	<ul style="list-style-type: none">true(if include_pag es=true)false	no	If true, the returned visits contain the associated pages. You can only use this parameter if include_pages is set to true.

Method	GET		
include_events	<ul style="list-style-type: none">• true• false	no	If true, the returned visits contain the reference list of associated events.
include_events_detail	<ul style="list-style-type: none">• true (if include_events=true)• false	no	If true, the returned visits contain the associated events. You can only use this parameter if include_events is set to true.

Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this request can return.

HTTP code	200
HTTP Title	OK
Body	JSON Array of Visit resources .