

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Deployment Guide

cep Section

cep Section

Settings for Complex Event Processing (CEP).

Contents

- 1 cep Section
 - 1.1 domainSeparation
 - 1.2 cepSessionCacheSize
 - 1.3 cepSessionCacheTtl

Deployment Guide 2

domainSeparation

Description: Specifies whether the DROOLS knowledge base should be separated by domains and

sub-domains.

Default Value: false **Valid Values:** true, false

Mandatory: No

Changes Take Effect: After server restart

cepSessionCacheSize

Description: Defines the size of the cache that is used for storing DRL sessions. This value should be

not less than expected maximum count of simultaneous visits on a particular server.

Default Value: 10000

Valid Values: positive integer greater than 100

Mandatory: No

Changes Take Effect: After server restart

cepSessionCacheTtl

Description: Inactivity timeout (in seconds) on the DRL session. After the timeout value is reached,

the session is treated as invalid and removed from cache.

Default Value: 600

Valid Values: positive integer greater than 300

Mandatory: No

Changes Take Effect: After server restart

Deployment Guide 3