



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Deployment Guide

kibana Section

12/19/2025

Contents

- 1 kibana Section
 - 1.1 elasticsearch_url
 - 1.2 enabled
 - 1.3 port

kibana Section

elasticsearch_url

Description: Specifies the location of the Elasticsearch HTTP port. **Note:** The Elasticsearch port is not specified in the default settings for external Cassandra. Because of this, you should use the default value of 9200. If you need to use a different port for Elasticsearch, use the `-Des.http.port` option to set that value. For more information, refer to [Deploy a Cassandra Cluster Node](#).

Mandatory: No

Default Value: `http://localhost:9200`

Valid Values: A valid URL that points to the Elasticsearch port

Changes Take Effect: After start/restart

enabled

Description: Indicates whether the Kibana server is started during GWE Server startup. The Kibana server is used in the Advanced Reporting Dashboard.

Mandatory: No

Default Value: `true`

Valid Values: `true`, `false`

Changes Take Effect: After start/restart

port

Description: Specifies the port on which the Kibana server is listening. Used only if the Kibana server is started.

Mandatory: No

Default Value: `5601`

Valid Values: Any positive integer valid for specifying a port ID

Changes Take Effect: After start/restart