



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Deployment Guide

[privacy Section](#)

12/19/2025

privacy Section

Contents

- 1 privacy Section
 - 1.1 collectActualIPs
 - 1.2 collectForwardedIPs
 - 1.3 geoMode
 - 1.4 pathToGeoDB

collectActualIPs

Description: If true, the IP addresses of visitors will be collected and stored in the database.

Default Value: false

Valid Values: true, false

Mandatory: No

Changes Take Effect: After server restart

collectForwardedIPs

Description: If true, the IP addresses that the visitor arrived from will be collected and stored in the database.

Default Value: false

Valid Values: true, false

Mandatory: No

Changes Take Effect: After server restart

geoMode

Description: The precision of the geolocation service. **Note:** This option will only work if `collectActualIPs` is enabled.

Default Value: LOCATION

Valid Values: OFF, LOCATION

Mandatory: No

Changes Take Effect: After server restart

pathToGeoDB

Description: The path to the `MaxMind` GeoDB file.

Default Value: `./gwe/resources/geo/GeoLite2-City.mmdb`

Valid Values: Any valid path to a GeoDB file

Mandatory: No

Changes Take Effect: After server restart