

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Identity Resource

Identity Resource

Contents

- 1 Identity Resource
 - 1.1 Resource Details
 - 1.2 Related Requests
 - 1.3 Examples

The identity resource contains visitor information and is created when the Web Engagement Server receives the SignIn event. The Browser Tier generates this event when the visitor signs in (or is authenticated with the company web portal). The identification information submitted by the visitor is used to create the identity ID (for instance, the email address or an account name).

At this point, the identification scope of the visitor is Authenticated. If the visitor signs out, the Web Engagement Server receives the SignOut event and the identification scope becomes Recognized. For further information on events, see Event Resource.

Resource Details

Field	Туре	Mandatory	Description
identityId	string	yes	The unique ID of the given identity. The visitor provides the identityId information when registering on the website; for instance, it can be the email address.
name	string	no	User name.
location	string	no	User location.
entityInCS	string	no	Entity in the Contact Server.
visitScope	Authenticated, Recognized	yes	Specify the visit's identification scope in relation to the visitor. If the visitor is authenticated, you can retrieve session information. If the visitor signs out, the visit scope changes to recognized.
eventIds	string[]	no	Array of event IDs associated with this identity.
events	event[]	no	Array of the event resources associated with this identity.
pagelds	string[]	no	Array of page IDs associated with this identity.
pages	page[]	no	Array of the page resources associated with this identity.
visitIds	string[]	no	Array of visit IDs associated with this

Field	Туре	Mandatory	Description
			identity.
visits	visit[]	no	Array of the visit resources associated with this identity.

Related Requests

- Query events by identity
- Query identity
- Query identities
- · Query pages by identity
- · Query visits by identity
- · Query identities by visit
- · Query user agents by identity

Examples

Retrieving Identities

The following request retrieves all the identities available.

Request

GET http://127.0.0.1:9081/server/data/identities

Response

```
HTTP/1.1 200 OK
Date: Wed, 12 Dec 2012 15:17:09 GMT
Content-Type: application/json; charset=UTF-8
Date: Wed, 12 Dec 2012 15:17:09 GMT
Accept-Ranges: bytes
Server: Restlet-Framework/2.1.0
Content-Length: 477
[{"eventIds":null, "events":null, "pageIds":null, "pages":null,
"sessionIds":null, "sessions":null, "identityId": "pat.thompsom@genesyslab.com",
"name":null, "location":null, "entityInCS":null, "visitScope": "Authenticated",
"visitIds":null, "visits":null},
{"eventIds":null, "events":null, "identityId": "user@genesyslab.com",
"name":null, "location":null, "entityInCS":null, "visitScope": "Authenticated",
"visitIds":null, "visits":null}]
```

Retrieving Identities with page IDs

The following request retrieves all the identities available, including the associated page IDs.

Request

GET /server/data/identities?include_pages=true

Response

```
HTTP/1.1 200 OK
Date: Wed, 12 Dec 2012 15:28:13 GMT
Content-Type: application/json; charset=UTF-8
Date: Wed, 12 Dec 2012 15:28:13 GMT
Accept-Ranges: bytes
Server: Restlet-Framework/2.1.0
Content-Length: 627
[{"eventIds":null,"events":null,
"pageIds":["11ff6de0-446e-11e2-bfd2-00505625a04f"],
"pages":null,"sessionIds":null,"sessions":null,"
identityId":"pat.thompsom@genesyslab.com",
"name":null,"location":null,"entityInCS":null,
"visitScope":"Authenticated","visitIds":null,
"visits":null},

{"eventIds":null,"events":null,
"pageIds":["45f0eda1-3fa4-11e2-aee5-00505625a04f","c489cac0-3fa3-11e2-aee5-00505625a04f",
"06afd7f0-3fa4-11e2-aee50505625a04f"],"pages":null,"sessionIds":null,
"sessions":null,"identityId":"user@genesyslab.com",
"name":null,"location":null,"entityInCS":null,"visitScope":"Authenticated",
"visitIds":null,"visits":null}]
```