



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## API Reference

Query identity

# Query identity

## Contents

- [1 Query identity](#)
  - [1.1 Description](#)
  - [1.2 Request](#)
  - [1.3 Response](#)
  - [1.4 Example](#)

## Description

This method retrieves a given identity.

## Request

Method	GET		
URL	/identities/\${identityId}		
Parameters			
Name	Value	Mandatory	Description
\${identityId}	string	yes	Identity identifier.
include_visits	<ul style="list-style-type: none"><li>• true</li><li>• false</li></ul>	no	If true, the returned identity contains the reference list of associated visits.
include_visits_detail	<ul style="list-style-type: none"><li>• true (if include_visits=true)</li><li>• false</li></ul>	no	If true, the returned identity contains the associated visit resources. You can only use this parameter if include_visits is set to true.
include_pages	<ul style="list-style-type: none"><li>• true</li><li>• false</li></ul>	no	If true, the returned identity contains the reference list of the associated pages.
include_pages_detail	<ul style="list-style-type: none"><li>• true (if include_pages=true)</li><li>• false</li></ul>	no	If true, the returned identity contains the associated pages. You can only use this parameter if include_pages is set to true.
include_events	<ul style="list-style-type: none"><li>• true</li><li>• false</li></ul>	no	If true, the returned identity contains the reference list of associated events.
include_events_detail	<ul style="list-style-type: none"><li>• true (if include_events=true)</li><li>• false</li></ul>	no	If true, the returned identity contains the associated events. You can only use this parameter if include_events is set to true.

## Response

The History REST API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this request can return.

<b>HTTP code</b>	200
<b>HTTP Title</b>	OK
<b>Body</b>	<a href="#">JSON Identity</a> .

## Example

The following request retrieves the identity resource with the `pat.thompson@genesyslab.com` ID.

### Request

<http://127.0.0.1:9081/server/data/identities/pat.thompson@genesyslab.com>

### Response

```
HTTP/1.1 200 OK
Date: Wed, 12 Dec 2012 15:17:09 GMT
Content-Type: application/json; charset=UTF-8
Date: Wed, 12 Dec 2012 15:17:09 GMT
Accept-Ranges: bytes
Server: Restlet-Framework/2.1.0
Content-Length: 477
[{"eventIds":null,"events":null,"pageIds":null,"pages":null,
"sessionIds":null,"sessions":null,"identityId":"pat.thompson@genesyslab.com",
"name":null,"location":null,"entityInCS":null,"visitScope":"Authenticated",
"visitIds":null,"visits":null}]
```