



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## API Reference

[Visit Resource](#)

# Visit Resource

## Contents

- [1 Visit Resource](#)
  - [1.1 Description](#)
  - [1.2 Resource Details](#)
  - [1.3 Related Requests](#)
  - [1.4 Example](#)

## Description

The visit resource contains the information related to a visitor's visit, which is the browser session opened by the visitor to visit the website. The visit starts with the `VisitStarted` event (submitted by the website) and then, all the browsing activity is recorded in page and event resources associated with the visit. The visitor remains Anonymous until he or she authenticates on the website. When authentication occurs, the visit is associated with an identity resource.

### Important

Several identities are associated with the same visitId if several visitors authenticate on the website. See [Identity Resource](#).

## Resource Details

Field	Type	Mandatory	Description
visitId	string	yes	ID of the given visit.
startDate	long	yes	Date in milliseconds at which the visit started.
endDate	long	no	Date in milliseconds at which the visit ended; 0 means that the visit is not terminated.
globalVisitId	string	no	ID of the global visit.
userAgentId	string	no	ID of the associated user agent if any; otherwise, null.
eventIds	string[]	no	Array of event IDs associated with this visit.
events	<a href="#">event</a> []	no	Array of the event resources associated with this visit.
pageIds	string[]	no	Array of page IDs associated with this visit.
pages	<a href="#">page</a> []	no	Array of the page resources associated with this visit.

## Related Requests

- [Create new event for visit](#)
- [Create new visit](#)
- [Query events by visit](#)
- [Query identities by visit](#)
- [Query pages by visit](#)
- [Query visit](#)
- [Query visits by identity](#)

## Example

### Retrieve a Given Visit

#### Request

GET <http://127.0.0.1:9081/server/data/visits/f24c60f6-0728-4f3d-b8b4-1e7bad2dc8a3>

#### Response

```
HTTP/1.1 200 OK
Date: Wed, 12 Dec 2012 16:03:03 GMT
Content-Type: application/json; charset=UTF-8
Date: Wed, 12 Dec 2012 16:03:03 GMT
Accept-Ranges: bytes
Server: Restlet-Framework/2.1.0
Content-Length: 345
{"eventIds":null,"events":null,"pageIds":null,"pages":null,"
sessionIds":null,"sessions":null,
"visitId":"f24c60f6-0728-4f3d-b8b4-1e7bad2dc8a3",
"startDate":1354797882714,"endDate":0,
"activeSessionId":"00000000-0000-1000-8000-000000000000",
"globalVisitID":"c93a19a1-45db-4d59-9c85-b637daea4a20",
"userAgentId":"b4ec8ef0-3fa2-11e2-aee5-00505625a04f"}
```